

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 NEMA Premium Efficiency Three-Phase

Product code : 14285009

Catalog # : 15018OT3G444TSC-W40

Frame : 444/5TSC
 Output : 150 HP (110 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 460 V
 Rated current : 170 A
 L. R. Amperes : 1105 A
 LRC : 6.5x(Code G)
 No load current : 58.0 A
 Rated speed : 1784 rpm
 Slip : 0.89 %
 Rated torque : 442 ft.lb
 Locked rotor torque : 200 %
 Breakdown torque : 240 %
 Insulation class : F
 Service factor : 1.25
 Moment of inertia (J) : 42.1 sq.ft.lb
 Design : B

Locked rotor time : 39s (cold) 22s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP23
 Cooling method : IC01 - ODP
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 78.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 1336 lb

Output	25%		50%		75%		100%	
Efficiency (%)	95.3	94.8	95.4	94.9	95.8	95.3	95.8	95.3
	94.8	95.0	94.9	95.1	95.3	95.3	95.3	95.3
Power Factor	0.49	0.49	0.74	0.74	0.82	0.82	0.85	0.85
	0.45	0.42	0.70	0.68	0.80	0.78	0.84	0.83

Foundation loads
 Max. traction : 2749 lb
 Max. compression : 4085 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6212 Z C3
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	27 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	29/03/2024			
		Revision		