

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



| | | | | | | | |
|---|------------------------|---|------------------------|-------------------------------|--|--|--|
| Customer : | | | | | | | |
| Product line | | : W40 NEMA Premium Efficiency Three-Phase | | Product code : 14284557 | | | |
| | | | | Catalog # : 10012OT3E444T-W40 | | | |
| Frame | : 444/5T | Locked rotor time | : 23s (cold) 13s (hot) | | | | |
| Output | : 100 HP (75 kW) | Temperature rise | : 80 K | | | | |
| Poles | : 6 | Duty cycle | : Cont.(S1) | | | | |
| Frequency | : 60 Hz | Ambient temperature | : -20°C to +40°C | | | | |
| Rated voltage | : 230/460 V | Altitude | : 1000 m.a.s.l. | | | | |
| Rated current | : 254/127 A | Protection degree | : IP23 | | | | |
| L. R. Amperes | : 1549/775 A | Cooling method | : IC01 - ODP | | | | |
| LRC | : 6.1x(Code G) | Mounting | : F-1 | | | | |
| No load current | : 113/56.5 A | Rotation ¹ | : Both (CW and CCW) | | | | |
| Rated speed | : 1190 rpm | Noise level ² | : 69.0 dB(A) | | | | |
| Slip | : 0.83 % | Starting method | : Direct On Line | | | | |
| Rated torque | : 441 ft.lb | Approx. weight ³ | : 1339 lb | | | | |
| Locked rotor torque | : 200 % | | | | | | |
| Breakdown torque | : 250 % | | | | | | |
| Insulation class | : F | | | | | | |
| Service factor | : 1.25 | | | | | | |
| Moment of inertia (J) | : 60.6 sq.ft.lb | | | | | | |
| Design | : B | | | | | | |
| Output | 25% | 50% | 75% | 100% | | | |
| Efficiency (%) | 94.4 | 93.6 | 94.5 | 93.7 | | | |
| | 92.8 | 91.9 | 93.0 | 92.4 | | | |
| Power Factor | 0.37 | 0.34 | 0.61 | 0.56 | | | |
| | 0.31 | 0.29 | 0.53 | 0.50 | | | |
| | | | | 0.65 | | | |
| | | | | 0.61 | | | |
| | | | | 0.75 | | | |
| | | | | 0.73 | | | |
| Foundation loads | | | | | | | |
| Max. traction | | : 2406 lb | | | | | |
| Max. compression | | : 3745 lb | | | | | |
| Drive end | | | | | | | |
| Bearing type | : 6319 C3 | Non drive end | | | | | |
| Sealing | : Without Bearing Seal | 6314 C3 | | | | | |
| Lubrication interval | : 20000 h | Without Bearing Seal | | | | | |
| Lubricant amount | : 45 g | 20000 h | | | | | |
| Lubricant type | : Mobil Polyrex EM | 27 g | | | | | |
| Notes: | | | | | | | |
| This revision replaces and cancel the previous one, which must be eliminated. | | | | | | | |
| (1) Looking the motor from the shaft end. | | | | | | | |
| (2) Measured at 1m and with tolerance of +3dB(A). | | | | | | | |
| (3) Approximate weight subject to changes after manufacturing process. | | | | | | | |
| (4) At 100% of full load. | | | | | | | |
| Rev. | Changes Summary | | | Performed | | | |
| | | | | Checked | | | |
| Performed by | | | | | | | |
| Checked by | | | | | | | |
| Date | 29/03/2024 | | | | | | |
| | | Page | Revision | | | | |
| | | 1 / 1 | | | | | |