

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 NEMA Premium Efficiency Three-Phase

Product code : 14285010

Catalog # : 15018OT3G444TSDF2-W4

Frame : 444/5TSD
Output : 150 HP (110 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 460 V
Rated current : 170 A
L. R. Amperes : 1105 A
LRC : 6.5x(Code G)
No load current : 58.0 A
Rated speed : 1784 rpm
Slip : 0.89 %
Rated torque : 442 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 240 %
Insulation class : F
Service factor : 1.25
Moment of inertia (J) : 42.1 sq.ft.lb
Design : B

Locked rotor time : 39s (cold) 22s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : F-2
Rotation¹ : Both (CW and CCW)
Noise level² : 78.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 1352 lb

Output	25%	50%	75%	100%				
Efficiency (%)	95.3	94.8	95.4	94.9	95.8	95.3	95.8	95.3
Power Factor	0.49	0.49	0.74	0.74	0.82	0.82	0.85	0.85
	0.45	0.42	0.70	0.68	0.80	0.78	0.84	0.83

Foundation loads
Max. traction : 2741 lb
Max. compression : 4093 lb

	Drive end	Non drive end
Bearing type	6314 C3	6212 Z C3
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	20000 h	20000 h
Lubricant amount	27 g	13 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	29/03/2024			
		Revision		