

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Premium Efficiency Three-Phase

Product code : 14013927

Catalog # : .7518ET3J56-S

Frame : 56
Output : 0.75 HP (0.55 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 380/660 V
Rated current : 1.44/0.829 A
L. R. Amperes : 11.1/6.38 A
LRC : 7.7x(Code L)
No load current : 0.995/0.573 A
Rated speed : 1760 rpm
Slip : 2.22 %
Rated torque : 2.24 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 360 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.0854 sq.ft.lb

Locked rotor time : 28s (cold) 16s (hot)
Temperature rise : 70 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +50°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 52.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 27.7 lb

Output	25%	50%	75%	100%
Efficiency (%)	0.000	75.5	80.0	81.5
Power Factor	0.00	0.49	0.62	0.71

Foundation loads
Max. traction : 65 lb
Max. compression : 93 lb

	Drive end	Non drive end
Bearing type :	6203 ZZ	6202 ZZ
Sealing :	V'Ring	Without Bearing Seal
Lubrication interval :	0 h	0 h
Lubricant amount :	0 g	0 g
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		