

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :						
Product line	: W40 NEMA Premium Efficiency Three-Phase		Product code :	14270944		
			Catalog # :	07518OT3G365TS-W40		
Frame	: 364/5TS	Locked rotor time	: 25s (cold) 14s (hot)			
Output	: 75 HP (55 kW)	Temperature rise	: 80 K			
Poles	: 4	Duty cycle	: Cont.(S1)			
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C			
Rated voltage	: 460 V	Altitude	: 1000 m.a.s.l.			
Rated current	: 85.5 A	Protection degree	: IP23			
L. R. Amperes	: 581 A	Cooling method	: IC01 - ODP			
LRC	: 6.8x(Code G)	Mounting	: F-1			
No load current	: 30.5 A	Rotation ¹	: Both (CW and CCW)			
Rated speed	: 1780 rpm	Noise level ²	: 69.0 dB(A)			
Slip	: 1.11 %	Starting method	: Direct On Line			
Rated torque	: 221 ft.lb	Approx. weight ³	: 769 lb			
Locked rotor torque	: 220 %					
Breakdown torque	: 260 %					
Insulation class	: F					
Service factor	: 1.25					
Moment of inertia (J)	: 16.8 sq.ft.lb					
Design	: B					
Output	25%	50%	75%	100%		
Efficiency (%)	94.4	93.7	94.5	93.8		
	93.7	93.7	93.8	93.8		
Power Factor	0.48	0.48	0.73	0.73		
	0.43	0.40	0.69	0.66		
		Drive end	Non drive end			
Bearing type	: 6314 C3		6212 Z C3			
Sealing	: Without Bearing Seal		Without Bearing Seal			
Lubrication interval	: 20000 h		20000 h			
Lubricant amount	: 27 g		13 g			
Lubricant type	: Mobil Polyrex EM					
Notes:						
This revision replaces and cancel the previous one, which must be eliminated.						
(1) Looking the motor from the shaft end.						
(2) Measured at 1m and with tolerance of +3dB(A).						
(3) Approximate weight subject to changes after manufacturing process.						
(4) At 100% of full load.						
Rev.	Changes Summary			Performed		
				Checked		
Performed by						
Checked by						
Date	28/03/2024					
			Page	Revision		
			1 / 1			