

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :					
Product line	: Rolled Steel NEMA Premium Efficiency Three-Phase	Product code :	12674774		
		Catalog # :	00536OT3H182T-S		
Frame	: 182/4T	Locked rotor time	: 27s (cold) 15s (hot)		
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K		
Poles	: 2	Duty cycle	: Cont.(S1)		
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.		
Rated current	: 5.06 A	Cooling method	: IC01 - ODP		
L. R. Amperes	: 38.4 A	Mounting	: F-1		
LRC	: 7.6x(Code J)	Rotation <sup>1</sup>	: Both (CW and CCW)		
No load current	: 2.48 A	Noise level <sup>2</sup>	: 65.0 dB(A)		
Rated speed	: 3510 rpm	Starting method	: Direct On Line		
Slip	: 2.50 %	Approx. weight <sup>3</sup>	: 59.1 lb		
Rated torque	: 7.48 ft.lb				
Locked rotor torque	: 190 %				
Breakdown torque	: 300 %				
Insulation class	: F				
Service factor	: 1.15				
Moment of inertia (J)	: 0.1386 sq.ft.lb				
Design	: B				
Output	50%	75%	100%		
Efficiency (%)	85.5	86.5	86.5		
Power Factor	0.66	0.78	0.85		
Foundation loads					
		Max. traction	: 114 lb		
		Max. compression	: 173 lb		
Drive end		Non drive end			
Bearing type	: 6206 ZZ		6205 ZZ		
Sealing	: Without Bearing Seal	Without Bearing Seal			
Lubrication interval	: -	-			
Lubricant amount	: -	-			
Lubricant type	: Mobil Polyrex EM				
Notes:					
This revision replaces and cancel the previous one, which must be eliminated.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
(1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.					
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1 / 1	