

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :																																																																																														
Product line	: Rolled Steel NEMA Premium Efficiency Three-Phase		Product code :	12677336																																																																																										
				Catalog # : 00536ET3ER184TC-S																																																																																										
<table> <tr><td>Frame</td><td>:</td><td>182/4TC</td><td>Locked rotor time</td><td>: 34s (cold) 19s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>5 HP (3.7 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>2</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>11.8/5.90 A</td><td>Protection degree</td><td>: IP55</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>92.0/46.0 A</td><td>Cooling method</td><td>: IC411 - TEFC</td></tr> <tr><td>LRC</td><td>:</td><td>7.8x(Code J)</td><td>Mounting</td><td>: W-6</td></tr> <tr><td>No load current</td><td>:</td><td>4.40/2.20 A</td><td>Rotation<sup>1</sup></td><td>: Both (CW and CCW)</td></tr> <tr><td>Rated speed</td><td>:</td><td>3500 rpm</td><td>Noise level<sup>2</sup></td><td>: 68.0 dB(A)</td></tr> <tr><td>Slip</td><td>:</td><td>2.78 %</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Rated torque</td><td>:</td><td>7.50 ft.lb</td><td>Approx. weight<sup>3</sup></td><td>: 89.8 lb</td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>220 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>300 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.15</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.2079 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>:</td><td>B</td><td></td><td></td></tr> </table>				Frame	:	182/4TC	Locked rotor time	: 34s (cold) 19s (hot)	Output	:	5 HP (3.7 kW)	Temperature rise	: 80 K	Poles	:	2	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	11.8/5.90 A	Protection degree	: IP55	L. R. Amperes	:	92.0/46.0 A	Cooling method	: IC411 - TEFC	LRC	:	7.8x(Code J)	Mounting	: W-6	No load current	:	4.40/2.20 A	Rotation <sup>1</sup>	: Both (CW and CCW)	Rated speed	:	3500 rpm	Noise level <sup>2</sup>	: 68.0 dB(A)	Slip	:	2.78 %	Starting method	: Direct On Line	Rated torque	:	7.50 ft.lb	Approx. weight <sup>3</sup>	: 89.8 lb	Locked rotor torque	:	220 %			Breakdown torque	:	300 %			Insulation class	:	F			Service factor	:	1.15			Moment of inertia (J)	:	0.2079 sq.ft.lb			Design	:	B			
Frame	:	182/4TC	Locked rotor time	: 34s (cold) 19s (hot)																																																																																										
Output	:	5 HP (3.7 kW)	Temperature rise	: 80 K																																																																																										
Poles	:	2	Duty cycle	: Cont.(S1)																																																																																										
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																										
Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.																																																																																										
Rated current	:	11.8/5.90 A	Protection degree	: IP55																																																																																										
L. R. Amperes	:	92.0/46.0 A	Cooling method	: IC411 - TEFC																																																																																										
LRC	:	7.8x(Code J)	Mounting	: W-6																																																																																										
No load current	:	4.40/2.20 A	Rotation <sup>1</sup>	: Both (CW and CCW)																																																																																										
Rated speed	:	3500 rpm	Noise level <sup>2</sup>	: 68.0 dB(A)																																																																																										
Slip	:	2.78 %	Starting method	: Direct On Line																																																																																										
Rated torque	:	7.50 ft.lb	Approx. weight <sup>3</sup>	: 89.8 lb																																																																																										
Locked rotor torque	:	220 %																																																																																												
Breakdown torque	:	300 %																																																																																												
Insulation class	:	F																																																																																												
Service factor	:	1.15																																																																																												
Moment of inertia (J)	:	0.2079 sq.ft.lb																																																																																												
Design	:	B																																																																																												
Output	25%	50%	75%	100%	Foundation loads																																																																																									
Efficiency (%)	87.2	87.5	88.5	88.5	Max. traction : 99 lb																																																																																									
Power Factor	0.49	0.76	0.85	0.89	Max. compression : 188 lb																																																																																									
<table> <tr> <td colspan="2"></td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr> <td>Bearing type</td><td>:</td><td>6206 ZZ</td><td>6205 ZZ</td><td></td></tr> <tr> <td>Sealing</td><td>:</td><td>V'Ring</td><td colspan="2">Without Bearing Seal</td></tr> <tr> <td>Lubrication interval</td><td>:</td><td>-</td><td>-</td><td></td></tr> <tr> <td>Lubricant amount</td><td>:</td><td>-</td><td>-</td><td></td></tr> <tr> <td>Lubricant type</td><td>:</td><td colspan="3" rowspan="2">Mobil Polyrex EM</td></tr> </table>							Drive end	Non drive end		Bearing type	:	6206 ZZ	6205 ZZ		Sealing	:	V'Ring	Without Bearing Seal		Lubrication interval	:	-	-		Lubricant amount	:	-	-		Lubricant type	:	Mobil Polyrex EM																																																														
		Drive end	Non drive end																																																																																											
Bearing type	:	6206 ZZ	6205 ZZ																																																																																											
Sealing	:	V'Ring	Without Bearing Seal																																																																																											
Lubrication interval	:	-	-																																																																																											
Lubricant amount	:	-	-																																																																																											
Lubricant type	:	Mobil Polyrex EM																																																																																												
<p>Notes: USABLE @208V 13.1A SF 1.00 SFA 13.1A</p>																																																																																														
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.  (2) Measured at 1m and with tolerance of +3dB(A).  (3) Approximate weight subject to changes after manufacturing process.  (4) At 100% of full load.</p>			<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>																																																																																											
Rev.	Changes Summary			Performed	Checked	Date																																																																																								
Performed by					Page	Revision																																																																																								
Checked by																																																																																														
Date	27/03/2024				1 / 1																																																																																									
Customer :																																																																																														
Product line	: Rolled Steel NEMA Premium Efficiency Three-Phase		Product code :	12677336																																																																																										
				Catalog # : 00536ET3ER184TC-S																																																																																										
<table> <tr><td>Frame</td><td>:</td><td>182/4TC</td><td>Locked rotor time</td><td>: 34s (cold) 19s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>5 HP (3.7 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>2</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>230/460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>11.8/5.90 A</td><td>Protection degree</td><td>: IP55</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>92.0/46.0 A</td><td>Cooling method</td><td>: IC411 - TEFC</td></tr> <tr><td>LRC</td><td>:</td><td>7.8x(Code J)</td><td>Mounting</td><td>: W-6</td></tr> <tr><td>No load current</td><td>:</td><td>4.40/2.20 A</td><td>Rotation<sup>1</sup></td><td>: Both (CW and CCW)</td></tr> <tr><td>Rated speed</td><td>:</td><td>3500 rpm</td><td>Noise level<sup>2</sup></td><td>: 68.0 dB(A)</td></tr> <tr><td>Slip</td><td>:</td><td>2.78 %</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Rated torque</td><td>:</td><td>7.50 ft.lb</td><td>Approx. weight<sup>3</sup></td><td>: 89.8 lb</td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>220 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>300 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.15</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.2079 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>:</td><td>B</td><td></td><td></td></tr> </table>				Frame	:	182/4TC	Locked rotor time	: 34s (cold) 19s (hot)	Output	:	5 HP (3.7 kW)	Temperature rise	: 80 K	Poles	:	2	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	11.8/5.90 A	Protection degree	: IP55	L. R. Amperes	:	92.0/46.0 A	Cooling method	: IC411 - TEFC	LRC	:	7.8x(Code J)	Mounting	: W-6	No load current	:	4.40/2.20 A	Rotation <sup>1</sup>	: Both (CW and CCW)	Rated speed	:	3500 rpm	Noise level <sup>2</sup>	: 68.0 dB(A)	Slip	:	2.78 %	Starting method	: Direct On Line	Rated torque	:	7.50 ft.lb	Approx. weight <sup>3</sup>	: 89.8 lb	Locked rotor torque	:	220 %			Breakdown torque	:	300 %			Insulation class	:	F			Service factor	:	1.15			Moment of inertia (J)	:	0.2079 sq.ft.lb			Design	:	B			
Frame	:	182/4TC	Locked rotor time	: 34s (cold) 19s (hot)																																																																																										
Output	:	5 HP (3.7 kW)	Temperature rise	: 80 K																																																																																										
Poles	:	2	Duty cycle	: Cont.(S1)																																																																																										
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																										
Rated voltage	:	230/460 V	Altitude	: 1000 m.a.s.l.																																																																																										
Rated current	:	11.8/5.90 A	Protection degree	: IP55																																																																																										
L. R. Amperes	:	92.0/46.0 A	Cooling method	: IC411 - TEFC																																																																																										
LRC	:	7.8x(Code J)	Mounting	: W-6																																																																																										
No load current	:	4.40/2.20 A	Rotation <sup>1</sup>	: Both (CW and CCW)																																																																																										
Rated speed	:	3500 rpm	Noise level <sup>2</sup>	: 68.0 dB(A)																																																																																										
Slip	:	2.78 %	Starting method	: Direct On Line																																																																																										
Rated torque	:	7.50 ft.lb	Approx. weight <sup>3</sup>	: 89.8 lb																																																																																										
Locked rotor torque	:	220 %																																																																																												
Breakdown torque	:	300 %																																																																																												
Insulation class	:	F																																																																																												
Service factor	:	1.15																																																																																												
Moment of inertia (J)	:	0.2079 sq.ft.lb																																																																																												
Design	:	B																																																																																												
Output	25%	50%	75%	100%	Foundation loads																																																																																									
Efficiency (%)	87.2	87.5	88.5	88.5	Max. traction	: 99 lb																																																																																								
Power Factor	0.49	0.76	0.85	0.89	Max. compression	: 188 lb																																																																																								
<table> <tr> <td colspan="2"></td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr> <td>Bearing type</td><td>:</td><td>6206 ZZ</td><td>6205 ZZ</td><td></td></tr> <tr> <td>Sealing</td><td>:</td><td>V'Ring</td><td colspan="2">Without Bearing Seal</td></tr> <tr> <td>Lubrication interval</td><td>:</td><td>-</td><td>-</td><td></td></tr> <tr> <td>Lubricant amount</td><td>:</td><td>-</td><td>-</td><td></td></tr> <tr> <td>Lubricant type</td><td>:</td><td colspan="3" rowspan="2">Mobil Polyrex EM</td></tr> </table>							Drive end	Non drive end		Bearing type	:	6206 ZZ	6205 ZZ		Sealing	:	V'Ring	Without Bearing Seal		Lubrication interval	:	-	-		Lubricant amount	:	-	-		Lubricant type	:	Mobil Polyrex EM																																																														
		Drive end	Non drive end																																																																																											
Bearing type	:	6206 ZZ	6205 ZZ																																																																																											
Sealing	:	V'Ring	Without Bearing Seal																																																																																											
Lubrication interval	:	-	-																																																																																											
Lubricant amount	:	-	-																																																																																											
Lubricant type	:	Mobil Polyrex EM																																																																																												
<p>Notes: USABLE @208V 13.1A SF 1.00 SFA 13.1A</p>																																																																																														
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.  (2) Measured at 1m and with tolerance of +3dB(A).  (3) Approximate weight subject to changes after manufacturing process.  (4) At 100% of full load.</p>			<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>																																																																																											
Rev.	Changes Summary			Performed	Checked	Date																																																																																								
Performed by					Page	Revision																																																																																								
Checked by																																																																																														
Date	27/03/2024				1 / 1																																																																																									