

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Premium Efficiency Three-Phase

Product code : 12809661

Catalog # : 00118OT3H56CFL-S

Frame : 56C
 Output : 1 HP (0.75 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 575 V
 Rated current : 1.26 A
 L. R. Amperes : 9.55 A
 LRC : 7.6x(Code L)
 No load current : 0.880 A
 Rated speed : 1760 rpm
 Slip : 2.22 %
 Rated torque : 2.98 ft.lb
 Locked rotor torque : 280 %
 Breakdown torque : 320 %
 Insulation class : F
 Service factor : 1.15
 Moment of inertia (J) : 0.0842 sq.ft.lb
 Design : A

Locked rotor time : 30s (cold) 17s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Cooling method : IC01 - ODP
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 52.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 26.3 lb

Output	25%	50%	75%	100%
Efficiency (%)	77.3	78.5	82.5	83.5
Power Factor	0.27	0.49	0.63	0.72

Foundation loads
 Max. traction : 80 lb
 Max. compression : 107 lb

	Drive end	Non drive end
Bearing type :	6204 ZZ	6202 ZZ
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	-	-
Lubricant amount :	-	-
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.
 (1) Looking the motor from the shaft end.
 (2) Measured at 1m and with tolerance of +3dB(A).
 (3) Approximate weight subject to changes after manufacturing process.
 (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		