DATA SHEET



Three Phase	e Indud	ction Mo	otor - S	Squirrel	Cage		
Customer	:						
Product line	: W22 Phas	•	ower High	Efficiency 1	hree-	Product code :	12176621
						Catalog # :	02589EP3QCT286VF1- W2
Frame		: 284/6	Γ		Locke	ed rotor time	: 16s (cold) 9s (hot)
Output		: 25 HP (18.5 kW)			Temperature rise		: 80 K
Poles		: 4			Duty cycle		: Cont.(S1)
Frequency		: 60 Hz			Ambient temperature		: -20°C to +40°C
Rated voltage		: 460 V			Altitud	-	: 1000 m.a.s.l.
Rated current		: 30.1 A	١			ction degree	: IP55
L. R. Amperes		: 256 A				ng method	: IC411 - TEFC
LRC		: 8.5x(C			Moun		: F-1
No load current		: 12.8 A			Rotati		: Both (CW and CCW)
Rated speed		: 1780 r	•			level ²	: 64.0 dB(A)
Slip		: 1.11 %	-			ng method	: Direct On Line
Rated torque		: 73.8 ft			Appro	x. weight³	: 468 lb
Locked rotor torqu		: 300 %					
Breakdown torque	;	: 310 %)				
Insulation class		: F					
Service factor	, n	: 1.15	<i>a.</i>				
Moment of inertia	(J)	: 5.85 s	q.ft.lb				
Output	25%	50%	75%	100%	Founda	tion loads	
Efficiency (%)	88.2 81.3	88.5 82.5	91.7 85.5	91.7 86.5	Max. tra	action	: 89 lb
Power Factor	0.43 0.23	0.68 0.40	0.80 0.52	0.84 0.60	Max. co	mpression	: 557 lb
			Drive 6			Non drive end	
Bearing type		:	6311 21			6211 2RS C3	
Cooling			\/'D	in a		\/'Dina	

Sealing V'Ring V'Ring Lubrication interval

Lubricant amount

Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Pha	se Inductio	n Motor - Squirrel Cage			
Customer	:				
Voltage: 110-127	7/200-240 V	Space heater informa	ation		
Voltage: 110-127	7200-240 V				
Rev.		Changes Summary	Performed	Checked	Date
					_
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	