

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 NEMA Premium Efficiency Three-Phase

Product code : 14045967

Catalog # : 07512OT3E405T-W40

Frame : 404/5T
Output : 75 HP (55 kW)
Poles : 6
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 172/85.9 A
L. R. Amperes : 1151/576 A
LRC : 6.7x(Code G)
No load current : 60.0/30.0 A
Rated speed : 1185 rpm
Slip : 1.25 %
Rated torque : 332 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 270 %
Insulation class : F
Service factor : 1.25
Moment of inertia (J) : 31.6 sq.ft.lb
Design : B

Locked rotor time : 19s (cold) 11s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 68.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 999 lb

Output	25%	50%	75%	100%				
Efficiency (%)	94.0	93.2	94.1	93.3	94.5	93.7	94.5	93.7
Power Factor	0.47	0.49	0.72	0.75	0.81	0.83	0.85	0.86
	0.45	0.42	0.71	0.68	0.81	0.79	0.85	0.84

Foundation loads
Max. traction : 2378 lb
Max. compression : 3377 lb

	Drive end	Non drive end
Bearing type	6316 C3	6212 Z C3
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	20000 h	20000 h
Lubricant amount	34 g	13 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			

Page 1 / 1
Revision