

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower NEMA Premium
Efficiency Three-Phase

Product code : 14413122

Catalog # : 00218ET3HCT145TF1-W2

Frame : 143/5T
Output : 2 HP (1.5 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 2.23 A
L. R. Amperes : 18.5 A
LRC : 8.3x(Code L)
No load current : 1.30 A
Rated speed : 1750 rpm
Slip : 2.78 %
Rated torque : 6.00 ft.lb
Locked rotor torque : 270 %
Breakdown torque : 320 %
Insulation class : F
Service factor : 1.25
Moment of inertia (J) : 0.1561 sq.ft.lb
Design : B

Locked rotor time : 18s (cold) 10s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 51.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 53.4 lb

Output 25% 50% 75% 100%

Efficiency (%) 85.2 85.5 86.5 86.5
Power Factor 0.32 0.57 0.70 0.78

Foundation loads

Max. traction : 140 lb
Max. compression : 194 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
15.0	12.8	12.1	8.4	6.0	4.7	3.5

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type :		6205 2RS	6204 2RS
Sealing :		V'Ring	V'Ring
Lubrication interval :		-	-
Lubricant amount :		-	-
Lubricant type :		Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	28/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	28/03/2024				