

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																																																																																
Product line	: W40 NEMA Premium Efficiency Three-Phase		Product code :	14270959																																																																																																												
				Catalog # : 07536OT3H364TS-W40																																																																																																												
<table> <tr><td>Frame</td><td>:</td><td>364/5TS</td><td>Locked rotor time</td><td>:</td><td>34s (cold) 19s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>75 HP (55 kW)</td><td>Temperature rise</td><td>:</td><td>80 K</td></tr> <tr><td>Poles</td><td>:</td><td>2</td><td>Duty cycle</td><td>:</td><td>Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>:</td><td>-20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>575 V</td><td>Altitude</td><td>:</td><td>1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>67.8 A</td><td>Protection degree</td><td>:</td><td>IP23</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>448 A</td><td>Cooling method</td><td>:</td><td>IC01 - ODP</td></tr> <tr><td>LRC</td><td>:</td><td>6.6x(Code G)</td><td>Mounting</td><td>:</td><td>F-1</td></tr> <tr><td>No load current</td><td>:</td><td>17.2 A</td><td>Rotation¹</td><td>:</td><td>Both (CW and CCW)</td></tr> <tr><td>Rated speed</td><td>:</td><td>3555 rpm</td><td>Noise level²</td><td>:</td><td>84.0 dB(A)</td></tr> <tr><td>Slip</td><td>:</td><td>1.25 %</td><td>Starting method</td><td>:</td><td>Direct On Line</td></tr> <tr><td>Rated torque</td><td>:</td><td>111 ft.lb</td><td>Approx. weight³</td><td>:</td><td>719 lb</td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>200 %</td><td></td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>250 %</td><td></td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.25</td><td></td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>6.40 sq.ft.lb</td><td></td><td></td><td></td></tr> <tr><td>Design</td><td>:</td><td>B</td><td></td><td></td><td></td></tr> </table>				Frame	:	364/5TS	Locked rotor time	:	34s (cold) 19s (hot)	Output	:	75 HP (55 kW)	Temperature rise	:	80 K	Poles	:	2	Duty cycle	:	Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	:	-20°C to +40°C	Rated voltage	:	575 V	Altitude	:	1000 m.a.s.l.	Rated current	:	67.8 A	Protection degree	:	IP23	L. R. Amperes	:	448 A	Cooling method	:	IC01 - ODP	LRC	:	6.6x(Code G)	Mounting	:	F-1	No load current	:	17.2 A	Rotation ¹	:	Both (CW and CCW)	Rated speed	:	3555 rpm	Noise level ²	:	84.0 dB(A)	Slip	:	1.25 %	Starting method	:	Direct On Line	Rated torque	:	111 ft.lb	Approx. weight ³	:	719 lb	Locked rotor torque	:	200 %				Breakdown torque	:	250 %				Insulation class	:	F				Service factor	:	1.25				Moment of inertia (J)	:	6.40 sq.ft.lb				Design	:	B				
Frame	:	364/5TS	Locked rotor time	:	34s (cold) 19s (hot)																																																																																																											
Output	:	75 HP (55 kW)	Temperature rise	:	80 K																																																																																																											
Poles	:	2	Duty cycle	:	Cont.(S1)																																																																																																											
Frequency	:	60 Hz	Ambient temperature	:	-20°C to +40°C																																																																																																											
Rated voltage	:	575 V	Altitude	:	1000 m.a.s.l.																																																																																																											
Rated current	:	67.8 A	Protection degree	:	IP23																																																																																																											
L. R. Amperes	:	448 A	Cooling method	:	IC01 - ODP																																																																																																											
LRC	:	6.6x(Code G)	Mounting	:	F-1																																																																																																											
No load current	:	17.2 A	Rotation ¹	:	Both (CW and CCW)																																																																																																											
Rated speed	:	3555 rpm	Noise level ²	:	84.0 dB(A)																																																																																																											
Slip	:	1.25 %	Starting method	:	Direct On Line																																																																																																											
Rated torque	:	111 ft.lb	Approx. weight ³	:	719 lb																																																																																																											
Locked rotor torque	:	200 %																																																																																																														
Breakdown torque	:	250 %																																																																																																														
Insulation class	:	F																																																																																																														
Service factor	:	1.25																																																																																																														
Moment of inertia (J)	:	6.40 sq.ft.lb																																																																																																														
Design	:	B																																																																																																														
Output	25%	50%	75%	100%	Foundation loads																																																																																																											
Efficiency (%)	91.0	91.7	93.0	93.6	Max. traction : 589 lb																																																																																																											
Power Factor	0.56	0.77	0.84	0.87	Max. compression : 1308 lb																																																																																																											
<table> <tr><td colspan="2">Bearing type</td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr><td colspan="2">:</td><td>6314 C3</td><td colspan="2">6212 Z C3</td></tr> <tr><td colspan="2">Sealing</td><td>Without Bearing Seal</td><td colspan="2">Without Bearing Seal</td></tr> <tr><td colspan="2">Lubrication interval</td><td>14418 h</td><td colspan="2">20000 h</td></tr> <tr><td colspan="2">Lubricant amount</td><td>27 g</td><td colspan="2" rowspan="4">13 g</td></tr> <tr><td colspan="2">Lubricant type</td><td colspan="3" rowspan="3">Mobil Polyrex EM</td></tr> </table>					Bearing type		Drive end	Non drive end		:		6314 C3	6212 Z C3		Sealing		Without Bearing Seal	Without Bearing Seal		Lubrication interval		14418 h	20000 h		Lubricant amount		27 g	13 g		Lubricant type		Mobil Polyrex EM																																																																																
Bearing type		Drive end	Non drive end																																																																																																													
:		6314 C3	6212 Z C3																																																																																																													
Sealing		Without Bearing Seal	Without Bearing Seal																																																																																																													
Lubrication interval		14418 h	20000 h																																																																																																													
Lubricant amount		27 g	13 g																																																																																																													
Lubricant type		Mobil Polyrex EM																																																																																																														
Notes:																																																																																																																
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>																																																																																																																
Rev.	Changes Summary			Performed	Checked	Date																																																																																																										
Performed by					Page	Revision																																																																																																										
Checked by					1 / 1																																																																																																											
Date	28/03/2024																																																																																																															