DATA SHEET

:

Three Phase Induction Motor - Squirrel Cage



Customer

Product line	: W22 Cooling Tower High Efficienc Phase	y Three- Product code :	12173125	12173125	
		Catalog # :	01589EP3PCT284V2	2F1-W	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia	: 260 % : F : 1.15	Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation ¹ Noise level ² Starting method Approx. weight ³	: 25s (cold) 14s (hot : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCV : 64.0 dB(A) : Direct On Line : 2.2 lb		
Output Efficiency (%) Power Factor	25% 50% 75% 100% 85.9 69.0 87.5 71.0 88.5 77.0 90.2 79.0 0.44 0.18 0.71 0.35 0.80 0.42 0.84 0.5	-	: 258 lb : 261 lb		
Bearing type Sealing Lubrication interva Lubricant amount	Drive end : 6311 2RS C3 : V'Ring i -	<u>Non drive end</u> 6211 2RS C3 V'Ring -			
Lubricant type	: - : N	- /lobil Polyrex EM			
Lubricant type Notes: This revision replace must be eliminated (1) Looking the moi (2) Measured at 1m	ces and cancel the previous one, which tor from the shaft end. n and with tolerance of +3dB(A).	Aobil Polyrex EM			
Lubricant type Notes: This revision replace must be eliminated (1) Looking the moi (2) Measured at 1m	ces and cancel the previous one, which tor from the shaft end. n and with tolerance of +3dB(A). eight subject to changes after cess. load.	These are average values power supply, subject to th	e tolerances stipulated in N		
Lubricant type Notes: This revision replace nust be eliminated 1) Looking the mo 2) Measured at 1n 3) Approximate we manufacturing proc 4) At 100% of full I	ces and cancel the previous one, which tor from the shaft end. n and with tolerance of +3dB(A). eight subject to changes after cess.	These are average values power supply, subject to th MG-1.	e tolerances stipulated in N	JEMA	
Lubricant type Notes: This revision replace nust be eliminated 1) Looking the mo 2) Measured at 1n 3) Approximate we nanufacturing proc 4) At 100% of full I Rev.	ces and cancel the previous one, which tor from the shaft end. n and with tolerance of +3dB(A). eight subject to changes after cess. load.	These are average values power supply, subject to th MG-1.	e tolerances stipulated in N	JEMA	
Lubricant type Notes: This revision replace nust be eliminated 1) Looking the mo 2) Measured at 1n 3) Approximate we manufacturing proc 4) At 100% of full I	ces and cancel the previous one, which tor from the shaft end. n and with tolerance of +3dB(A). eight subject to changes after cess. load.	These are average values power supply, subject to th MG-1.	e tolerances stipulated in N	NEMA	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A. Subject to change without notice

DATA SHEET

Three Phase Induction Motor - Squirrel Cage

:

Customer

Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary		Performed	Checked	Date			
Performed by					•			
Checked by				Page	Revision			
Date	28/03/2024			2/2				
This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.								

Subject to change without notice

