## **DATA SHEET**

Date

28/03/2024



Customer	:						
Product line	: W22 NEMA Premium Efficiency Three- Product code :					11164580	
	Phase	nase			Catalog # :	15018ET3HRB445T-W22	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class		: 444/5T : 150 HP (110 kW) : 4 : 60 Hz : 575 V : 136 A : 898 A : 6.6x(Code G) : 46.4 A : 1784 rpm : 0.89 % : 442 ft.lb : 200 % : 250 % : F : 1.15		Catalog #:  Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³		15018ET3HRB445T-W22  : 48s (cold) 27s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 73.0 dB(A) : Direct On Line : 1741 lb	
Service factor Moment of inertia Design	ı (J) :	66.7 sq.ft.lb					
Output	50%	75% 10	0%	Foundati	ion loads		
Efficiency (%) Power Factor	95.4	95.8 95 0.82 0.8	5.8	Max. traction Max. compression		: 2072 lb : 3813 lb	
Losses at normati	ve operating po	ints (speed;torqu	ie), in perce	entage of ra	ated output power		
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0		),9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25
4.5	3.5	3.1		2.4	1.5	1.1	0.6
Bearing type : Sealing : Lubrication interval : Lubricant amount : Lubricant type :		<u>Drive end</u> NU-319 C3 WSeal 5000 h 45 g		bil Polyrex	Non drive end 6316 C3 WSeal 10000 h 34 g	<u>l</u>	
Notes:							
This revision replaces and cancel the previous one, which must be eliminated.  (1) Looking the motor from the shaft end.  (2) Measured at 1m and with tolerance of +3dB(A).  (3) Approximate weight subject to changes after manufacturing process.  (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.		Changes Sumn	nary		Performed	Checked	Date
		<u>_</u>	<u>-</u>				
Performed by					1		1
Checked by		7				Page	Revision

1/1