DATA SHEET



Three Phase induction Motor - Squirrer Cage								
Customer	:							
Product line	: W22 Phase	Cooling To	ower High	Efficiency 1	hree-	Product code : Catalog # :	12175359 06089EP3P0	CT365V-W22
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia)	: 364/57 : 60 HP : 4 : 60 Hz : 200 V : 166 A : 1330 A : 8.0x(C : 75.0 A : 1780 r : 1.11 % : 250 % : 320 % : F : 1.15 : 23.3 se	(45 kW) A code J) pm		Tempe Duty of Ambie Altitud Protec Coolin Mount Rotati Noise Startir	nt temperature e tion degree g method ing on ¹	: 14s (cold) (: 80 K : Cont.(S1) : -20°C to +4 : 1000 m.a.s : IP55 : IC411 - TE : F-2 : Both (CW (: 71.0 dB(A) : Direct On L	40°C s.l. FC and CCW)
Output Efficiency (%) Power Factor	90.3 85.4 9 0.42 0.23				Max. tra	ion loads ction mpression	: 638 lb : 641 lb	
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type	al	: : : :	<u>Drive 6</u> 6314 2I WS - - F	RS C3 eal	ESTER O	Non drive end 6314 2RS C3 WSeal - - L (WT/ ENS)		

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Pha	se Inductio	n Motor - Squirrel Cage			
Customer	:				
Voltage: 110-127	7/200-240 V	Space heater informa	ation		
Voltage: 110-127	7200-240 V				
Rev.		Changes Summary	Performed	Checked	Date
					_
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	