

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : General Single-Phase Product code : 10580309

Frame	: B56	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 0.37 kW (0.5 HP)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 7.80/3.90 A	Protection degree	: IP55
L. R. Amperes	: 42.9/21.5 A	Cooling method	: IC411 - TEFC
LRC	: 5.5x(Code L)	Mounting	: F-1
No load current	: 6.60/3.30 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1450 rpm	Noise level ²	: 50.0 dB(A)
Slip	: 3.33 %	Starting method	: Direct On Line
Rated torque	: 1.80 ft.lb	Approx. weight ³	: 26.8 lb
Locked rotor torque	: 300 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 0.0982 sq.ft.lb		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	51.9	55.0	62.0	66.0	Max. traction : 32 lb
Power Factor	0.24	0.44	0.54	0.63	Max. compression : 59 lb

	Drive end	Non drive end
Bearing type	: 6203 ZZ	6202 ZZ
Sealing	: V'Ring	V'Ring
Lubrication interval	: -	-
Lubricant amount	: -	-
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	25/03/2024				
				Page	Revision
				1 / 1	