DATA SHEET



Three Phase Ir	nduction M	otor - Squ	uirrel	Cage		
Customer	:					
Product line	: W22 Cooling Phase	Гower High Effi	iciency T	hree- Product co		14324023 01526EP3QCT286V-W22
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia (J)	: 12 : 60 H: : 460 \ : 6.44 : 21.3	HP (2.8 kW) Z Z Z A A Code E) A pm % ft.lb 6		Locked rotor time Temperature rise Duty cycle Ambient temperate Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	ure	: 162s (cold) 90s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 65.0 dB(A) : Direct On Line : 485 lb
Output 259	<u>% 50%</u> 4 90.9 80.0 91.0		0%	Foundation loads Max. traction		: 631 lb
) ()	4 90.9 80.0 91.0 6 0.44 0.44 0.70			Max. compression		: 1116 lb
Bearing type Sealing Lubrication interval Lubricant amount Lubricant type Notes:	: : : : : : : : : : : : : : : : : : : :	Drive end 6311 2RS V'Ring - -	C3	6211	rive end 2RS C3 Ring -	

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage						
Customer	:					
Voltage: 110-127	7/200-240 V	Space heater informa	ation			
Voltage: 110-127	7200-240 V					
Rev.		Changes Summary	Performed	Checked	Date	
					_	
Performed by						
Checked by				Page	Revision	
Date	28/03/2024			2/2		