

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 NEMA Premium Efficiency Three-Phase

Product code : 13570826

Catalog # : 30018OT3H447/9TSD-W4

Frame : 447/9TSD
Output : 300 HP (220 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 271 A
L. R. Amperes : 1926 A
LRC : 7.1x(Code H)
No load current : 84.0 A
Rated speed : 1780 rpm
Slip : 1.11 %
Rated torque : 885 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 229 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 56.1 sq.ft.lb
Design : B

Locked rotor time : 28s (cold) 16s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 77.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 1970 lb

Output 25% 50% 75% 100%

Efficiency (%) 95.7 95.8 95.8 95.8
Power Factor 0.52 0.76 0.83 0.85

Foundation loads

Max. traction : 4441 lb
Max. compression : 6412 lb

	Drive end	Non drive end
Bearing type :	6314 C3	6314 C3
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	20000 h	20000 h
Lubricant amount :	27 g	27 g
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	29/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2Revision	
Checked by					
Date	29/03/2024				