

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower High Efficiency Three-Phase

Product code : 12174932

Catalog # : 04089EP3QCT364V2-W22

Frame : 364/5T
Output : 40 HP (30 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 460 V
Rated current : 46.8 A
L. R. Amperes : 337 A
LRC : 7.2x(Code H)
No load current : 16.5 A
Rated speed : 1780 rpm
Slip : 1.11 %
Rated torque : 118 ft.lb
Locked rotor torque : 229 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 19.9 sq.ft.lb

Locked rotor time : 14s (cold) 8s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-2
Rotation¹ : Both (CW and CCW)
Noise level² : 71.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 858 lb

Output	25%	50%	75%	100%				
Efficiency (%)	88.1	76.5	89.5	77.0	91.0	81.5	92.4	81.5
Power Factor	0.49	0.22	0.74	0.43	0.83	0.55	0.87	0.64

Foundation loads
Max. traction : 78 lb
Max. compression : 936 lb

	Drive end	Non drive end
Bearing type	6314 2RS C3	6314 2RS C3
Sealing	WSeal	WSeal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	POLYREA ESTER OIL (WT/ ENS)	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	28/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	28/03/2024				
			2 / 2		