DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 NEMA Premium Efficiency Three-Product code: 13500625 Catalog #: 30012ET3GKD586/7-W22 Frame : 586/7T Locked rotor time : 54s (cold) 30s (hot) Output : 300 HP (220 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 460 V : 1000 m.a.s.l. Altitude Rated current : 360 A Protection degree : IP55 L. R. Amperes : 2124 A Cooling method : IC411 - TEFC LRC : 5.9x(Code G) Mounting : F-1 No load current : 165 A Rotation¹ : Both (CW and CCW) Rated speed : 1193 rpm Noise level² : 77.0 dB(A) Starting method Slip : 0.58 % : Direct On Line Rated torque : 1320 ft.lb Approx. weight³ : 3495 lb Locked rotor torque : 220 % Breakdown torque : 250 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 278 sq.ft.lb Design : A 25% 50% 75% 100% Output Foundation loads

Max. traction

Max. compression

Drive endNon drive endBearing type: NU-322 C36319 C3Sealing: Taconite LabyrinthTaconite LabyrinthLubrication interval: 7000 h13000 hLubricant amount: 60 g45 g

95.8

0.80

Lubricant type : Mobil Polyrex EM

95.8

0.75

Notes:

Efficiency (%)

Power Factor

This revision replaces and cancel the previous one, which must be eliminated.

(1) Looking the motor from the shaft end.

0.000

0.00

95.0

0.65

- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

: 5140 lb

: 8635 lb

Rev. Changes Summary Performed Checked Date

Performed by
Checked by
Date 27/03/2024
Page Revision
1 / 2

DATA SHEET

	П
Ш	Ш

Three Phase Induction Motor - Squirrel Cage				<u> </u>		
Customer	:					
Voltage: 200 - 24	10 V	Space heater infor	mation			
Rev.		Changes Summary	Performed	Checked	Date	
Dorformadhi		I				
Performed by Checked by				Page	Revision	

2/2

27/03/2024

Date