

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14407460

Catalog # : 01009XT3E284T

Frame	: 284T	Locked rotor time	: 54s (cold) 30s (hot)
Output	: 10 HP (7.5 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 26.8/13.4 A	Protection degree	: IP55
L. R. Amperes	: 161/80.4 A	Cooling method	: IC411 - TEFC
LRC	: 6.0x(Code H)	Mounting	: F-1
No load current	: 12.0/6.00 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 884 rpm	Noise level ²	: 54.0 dB(A)
Slip	: 1.78 %	Starting method	: Direct On Line
Rated torque	: 59.4 ft.lb	Approx. weight ³	: 467 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 7.20 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	91.4	92.5	91.0	91.0	91.7	90.2	91.0	88.5	Max. traction	: 484 lb
	92.2	91.6	91.0	91.0	91.0	91.0	89.5	90.2		
Power Factor	0.37	0.42	0.62	0.67	0.72	0.76	0.77	0.80	Max. compression	: 949 lb
	0.40	0.37	0.65	0.62	0.74	0.73	0.79	0.78		

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6311 C3	6211 C3
Sealing	:				Oil Seal	Lip Seal
Lubrication interval	:				20000 h	20000 h
Lubricant amount	:				18 g	11 g
Lubricant type	:				Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	28/03/2024				