

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :																																																																											
Product line	: W22 NEMA Premium Efficiency Three-Phase		Product code :	13619541																																																																							
				Catalog # : 00109ET3EPM182/4Y-W2																																																																							
<table> <tr><td>Frame</td><td>:</td><td>184YZ</td><td></td></tr> <tr><td>Output</td><td>:</td><td>1 HP (0.75 kW)</td><td></td></tr> <tr><td>Poles</td><td>:</td><td>8</td><td></td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td></td></tr> <tr><td>Rated voltage</td><td>:</td><td>208-230/460 V</td><td></td></tr> <tr><td>Rated current</td><td>:</td><td>5.10-4.61/2.31 A</td><td></td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>30.6-27.7/13.9 A</td><td></td></tr> <tr><td>LRC</td><td>:</td><td>6.0x(Code M)</td><td></td></tr> <tr><td>No load current</td><td>:</td><td>0.000-3.40/1.70 A</td><td></td></tr> <tr><td>Rated speed</td><td>:</td><td>875 rpm</td><td></td></tr> <tr><td>Slip</td><td>:</td><td>2.78 %</td><td></td></tr> <tr><td>Rated torque</td><td>:</td><td>6.00 ft.lb</td><td></td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>300 %</td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>350 %</td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.25</td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>0.3987 sq.ft.lb</td><td></td></tr> <tr><td>Design</td><td>:</td><td>B</td><td></td></tr> </table>				Frame	:	184YZ		Output	:	1 HP (0.75 kW)		Poles	:	8		Frequency	:	60 Hz		Rated voltage	:	208-230/460 V		Rated current	:	5.10-4.61/2.31 A		L. R. Amperes	:	30.6-27.7/13.9 A		LRC	:	6.0x(Code M)		No load current	:	0.000-3.40/1.70 A		Rated speed	:	875 rpm		Slip	:	2.78 %		Rated torque	:	6.00 ft.lb		Locked rotor torque	:	300 %		Breakdown torque	:	350 %		Insulation class	:	F		Service factor	:	1.25		Moment of inertia (J)	:	0.3987 sq.ft.lb		Design	:	B	
Frame	:	184YZ																																																																									
Output	:	1 HP (0.75 kW)																																																																									
Poles	:	8																																																																									
Frequency	:	60 Hz																																																																									
Rated voltage	:	208-230/460 V																																																																									
Rated current	:	5.10-4.61/2.31 A																																																																									
L. R. Amperes	:	30.6-27.7/13.9 A																																																																									
LRC	:	6.0x(Code M)																																																																									
No load current	:	0.000-3.40/1.70 A																																																																									
Rated speed	:	875 rpm																																																																									
Slip	:	2.78 %																																																																									
Rated torque	:	6.00 ft.lb																																																																									
Locked rotor torque	:	300 %																																																																									
Breakdown torque	:	350 %																																																																									
Insulation class	:	F																																																																									
Service factor	:	1.25																																																																									
Moment of inertia (J)	:	0.3987 sq.ft.lb																																																																									
Design	:	B																																																																									
Output	25%	50%	75%	100%																																																																							
Efficiency (%)	0.000	74.0	77.0	78.5																																																																							
Power Factor	0.00	0.32	0.42	0.52																																																																							
<table> <tr><td colspan="2">Foundation loads</td></tr> <tr><td colspan="2">Max. traction</td></tr> <tr><td colspan="2">Max. compression</td></tr> </table>					Foundation loads		Max. traction		Max. compression																																																																		
Foundation loads																																																																											
Max. traction																																																																											
Max. compression																																																																											
<table> <tr><td colspan="2">Drive end</td><td colspan="3">Non drive end</td></tr> <tr><td>Bearing type</td><td>:</td><td>6207 ZZ</td><td colspan="2">6206 ZZ</td></tr> <tr><td>Sealing</td><td>:</td><td>V'Ring</td><td colspan="2">V'Ring</td></tr> <tr><td>Lubrication interval</td><td>:</td><td>0 h</td><td colspan="2">0 h</td></tr> <tr><td>Lubricant amount</td><td>:</td><td>0 g</td><td colspan="2" rowspan="3">0 g</td></tr> <tr><td>Lubricant type</td><td>:</td><td colspan="3" rowspan="2">Mobil Polyrex EM</td></tr> </table>					Drive end		Non drive end			Bearing type	:	6207 ZZ	6206 ZZ		Sealing	:	V'Ring	V'Ring		Lubrication interval	:	0 h	0 h		Lubricant amount	:	0 g	0 g		Lubricant type	:	Mobil Polyrex EM																																											
Drive end		Non drive end																																																																									
Bearing type	:	6207 ZZ	6206 ZZ																																																																								
Sealing	:	V'Ring	V'Ring																																																																								
Lubrication interval	:	0 h	0 h																																																																								
Lubricant amount	:	0 g	0 g																																																																								
Lubricant type	:	Mobil Polyrex EM																																																																									
Notes:																																																																											
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>			<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>																																																																								
Rev.	Changes Summary			Performed																																																																							
				Checked																																																																							
Performed by																																																																											
Checked by																																																																											
Date	29/03/2024																																																																										
			Page	Revision																																																																							
			1 / 1																																																																								