DATA SHEET

Date

28/03/2024



Customer	:							
Product line		: W22 NEMA Premium Efficiency Thre Phase				Product code :	14383370 12536ET3H444TS-W22G	
	Thase					Catalog # :		
Frame		· 44	1/5TS		Locked	d rotor time	: 52s (cold) 29s (hot)
Output		: 125 HP				rature rise	: 80 K	
Poles		: 2			Duty cycle		: Cont.(S1)	
Frequency		: 60 Hz				nt temperature	: -20°C to	
Rated voltage		: 575 V : 107 A			Altitud		: 1000 m.a	ı.s.l.
Rated current		: 107 A : 708 A				tion degree	: IP55	EEC
L. R. Amperes LRC		: 708 A : 6.6x(Code G)			Cooling method Mounting		: IC411 - TEFC : F-1	
No load current		: 27.2 A			Rotatio		: Both (CW and CCW)	
Rated speed					Noise level ²		: 81.0 dB(A)	
			83 %		Starting method		: Direct On Line	
Rated torque : 18			84 ft.lb		Approx	c. weight³	: 1599 lb	
Locked rotor tord		: 200						
Breakdown torqu	ue	: 250) %					
Insulation class		: F	_					
Service factor Moment of inerti	a (I)	: 1.1 : 33	ວ 5 sq.ft.lb					
Design	a (3)	: B	J 54.II.ID					
Output	25%	50%	75%	100%	Foundation loads			
Efficiency (%)	93.0			Max. traction		: 425 lb		
Power Factor	0.59	0.82	0.87	0.89		npression	: 2025 lb	
osses at normal	tive operat	ting points	(speed-tore	nue) in nerc	entage of r	ated output power		
P1 (0,9;1,0)	P2 (0,5		P3 (0,25;1		0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.8	3.0)	2.5		3.1	1.4	1.1	0.5
				e end		Non drive end	<u>d</u>	
Bearing type :		:		14 C3	6314 C3			
Sealing : Lubrication interval :		:		/Seal 000 h	WSeal 4000 h			
Lubrication interval :		:		27 g	27 g			
Lubricant type :			Mobil Polyrex EM					
Notes:								
This revision repl		cancel the	previous o	ne, which		re average values		
must be eliminate		the shoft	and		power s MG-1.	upply, subject to th	ne tolerances stipi	ulated in NEMA
(1) Looking the m (2) Measured at				۸۱	MG-1.			
(3) Approximate								
manufacturing pr		5,000 10 011	angee ane.					
(4) At 100% of fu								
Rev.		Cl	nanges Sun	nmary		Performed	Checked	Date
Performed by								
Checked by							Page	Revision

1/1