

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Brake Motor NEMA Premium Efficiency Product code : 13474022
 Three-Phase Catalog # : 00209ET3EBM213T-W22

Frame	: 213/5T	Locked rotor time	: 70s (cold) 39s (hot)
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 6.78/3.39 A	Protection degree	: IP55
L. R. Amperes	: 46.8/23.4 A	Cooling method	: IC411 - TEFC
LRC	: 6.9x(Code L)	Mounting	: F-1
No load current	: 4.60/2.30 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 875 rpm	Noise level ²	: 52.0 dB(A)
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 12.0 ft.lb	Approx. weight ³	: 187 lb
Locked rotor torque	: 220 %		
Breakdown torque	: 290 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 1.79 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	81.0	82.5	84.0	85.5
Power Factor	0.24	0.45	0.55	0.65

Foundation loads

Max. traction : 102 lb
 Max. compression : 290 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
16.1	13.5	13.2	9.6	7.0	5.6	4.4

Drive end

Non drive end

Bearing type	:	6308 ZZ	6207 ZZ
Sealing	:	V'Ring	Lip Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

USABLE @208V 7.49A SF 1.15 SFA 8.62A

This revision replaces and cancel the previous one, which must be eliminated.


- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Brake information

Voltage: 220-240 V

Brake Torque: 92.2 ft.lb

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	29/03/2024			Page 2 / 2	Revision