

# DATA SHEET


## Three Phase Induction Motor - Squirrel Cage



Customer :																																																																																														
Product line		: W22 NEMA Premium Efficiency Three-Phase		Product code : 13500595																																																																																										
				Catalog # : 25009ET3GKD586/7-W22																																																																																										
<table> <tr><td>Frame</td><td>:</td><td>586/7T</td><td>Locked rotor time</td><td>: 72s (cold) 40s (hot)</td></tr> <tr><td>Output</td><td>:</td><td>250 HP (185 kW)</td><td>Temperature rise</td><td>: 80 K</td></tr> <tr><td>Poles</td><td>:</td><td>8</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr><td>Frequency</td><td>:</td><td>60 Hz</td><td>Ambient temperature</td><td>: -20°C to +40°C</td></tr> <tr><td>Rated voltage</td><td>:</td><td>460 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr><td>Rated current</td><td>:</td><td>315 A</td><td>Protection degree</td><td>: IP55</td></tr> <tr><td>L. R. Amperes</td><td>:</td><td>2552 A</td><td>Cooling method</td><td>: IC411 - TEFC</td></tr> <tr><td>LRC</td><td>:</td><td>8.1x(Code K)</td><td>Mounting</td><td>: F-1</td></tr> <tr><td>No load current</td><td>:</td><td>165 A</td><td>Rotation<sup>1</sup></td><td>: Both (CW and CCW)</td></tr> <tr><td>Rated speed</td><td>:</td><td>895 rpm</td><td>Noise level<sup>2</sup></td><td>: 75.0 dB(A)</td></tr> <tr><td>Slip</td><td>:</td><td>0.56 %</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr><td>Rated torque</td><td>:</td><td>1470 ft.lb</td><td>Approx. weight<sup>3</sup></td><td>: 4042 lb</td></tr> <tr><td>Locked rotor torque</td><td>:</td><td>200 %</td><td></td><td></td></tr> <tr><td>Breakdown torque</td><td>:</td><td>229 %</td><td></td><td></td></tr> <tr><td>Insulation class</td><td>:</td><td>F</td><td></td><td></td></tr> <tr><td>Service factor</td><td>:</td><td>1.15</td><td></td><td></td></tr> <tr><td>Moment of inertia (J)</td><td>:</td><td>394 sq.ft.lb</td><td></td><td></td></tr> <tr><td>Design</td><td>:</td><td>A</td><td></td><td></td></tr> </table>				Frame	:	586/7T	Locked rotor time	: 72s (cold) 40s (hot)	Output	:	250 HP (185 kW)	Temperature rise	: 80 K	Poles	:	8	Duty cycle	: Cont.(S1)	Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C	Rated voltage	:	460 V	Altitude	: 1000 m.a.s.l.	Rated current	:	315 A	Protection degree	: IP55	L. R. Amperes	:	2552 A	Cooling method	: IC411 - TEFC	LRC	:	8.1x(Code K)	Mounting	: F-1	No load current	:	165 A	Rotation <sup>1</sup>	: Both (CW and CCW)	Rated speed	:	895 rpm	Noise level <sup>2</sup>	: 75.0 dB(A)	Slip	:	0.56 %	Starting method	: Direct On Line	Rated torque	:	1470 ft.lb	Approx. weight <sup>3</sup>	: 4042 lb	Locked rotor torque	:	200 %			Breakdown torque	:	229 %			Insulation class	:	F			Service factor	:	1.15			Moment of inertia (J)	:	394 sq.ft.lb			Design	:	A			
Frame	:	586/7T	Locked rotor time	: 72s (cold) 40s (hot)																																																																																										
Output	:	250 HP (185 kW)	Temperature rise	: 80 K																																																																																										
Poles	:	8	Duty cycle	: Cont.(S1)																																																																																										
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C																																																																																										
Rated voltage	:	460 V	Altitude	: 1000 m.a.s.l.																																																																																										
Rated current	:	315 A	Protection degree	: IP55																																																																																										
L. R. Amperes	:	2552 A	Cooling method	: IC411 - TEFC																																																																																										
LRC	:	8.1x(Code K)	Mounting	: F-1																																																																																										
No load current	:	165 A	Rotation <sup>1</sup>	: Both (CW and CCW)																																																																																										
Rated speed	:	895 rpm	Noise level <sup>2</sup>	: 75.0 dB(A)																																																																																										
Slip	:	0.56 %	Starting method	: Direct On Line																																																																																										
Rated torque	:	1470 ft.lb	Approx. weight <sup>3</sup>	: 4042 lb																																																																																										
Locked rotor torque	:	200 %																																																																																												
Breakdown torque	:	229 %																																																																																												
Insulation class	:	F																																																																																												
Service factor	:	1.15																																																																																												
Moment of inertia (J)	:	394 sq.ft.lb																																																																																												
Design	:	A																																																																																												
Output	25%	50%	75%	100%	Foundation loads																																																																																									
Efficiency (%)	0.000	94.5	95.8	95.8	Max. traction : 5018 lb																																																																																									
Power Factor	0.00	0.60	0.71	0.77	Max. compression : 9060 lb																																																																																									
<table> <tr><td colspan="2">Bearing type</td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr><td colspan="2">:</td><td>NU-322 C3</td><td colspan="2">6319 C3</td></tr> <tr><td colspan="2">Sealing</td><td>Taconite Labyrinth</td><td colspan="2">Taconite Labyrinth</td></tr> <tr><td colspan="2">Lubrication interval</td><td>13000 h</td><td colspan="2">17000 h</td></tr> <tr><td colspan="2">Lubricant amount</td><td>60 g</td><td colspan="2" rowspan="4">45 g</td></tr> <tr><td colspan="2">Lubricant type</td><td colspan="3" rowspan="3">Mobil Polyrex EM</td></tr> </table>					Bearing type		Drive end	Non drive end		:		NU-322 C3	6319 C3		Sealing		Taconite Labyrinth	Taconite Labyrinth		Lubrication interval		13000 h	17000 h		Lubricant amount		60 g	45 g		Lubricant type		Mobil Polyrex EM																																																														
Bearing type		Drive end	Non drive end																																																																																											
:		NU-322 C3	6319 C3																																																																																											
Sealing		Taconite Labyrinth	Taconite Labyrinth																																																																																											
Lubrication interval		13000 h	17000 h																																																																																											
Lubricant amount		60 g	45 g																																																																																											
Lubricant type		Mobil Polyrex EM																																																																																												
Notes:																																																																																														
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>																																																																																														
Rev.	Changes Summary			Performed																																																																																										
				Checked																																																																																										
Performed by				Page																																																																																										
Checked by				Revision																																																																																										
Date	27/03/2024			1 / 2																																																																																										

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

### Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	27/03/2024			Page 2 / 2	Revision