

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Brake Motor NEMA Premium Efficiency Product code : 13473873
 Three-Phase Catalog # : 00109ET3EBM182T-W22

Frame	: 182/4T	Locked rotor time	: 39s (cold) 22s (hot)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 4.62/2.31 A	Protection degree	: IP55
L. R. Amperes	: 29.1/14.6 A	Cooling method	: IC411 - TEFC
LRC	: 6.3x(Code N)	Mounting	: F-1
No load current	: 4.00/2.00 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 880 rpm	Noise level ²	: 50.0 dB(A)
Slip	: 2.22 %	Starting method	: Direct On Line
Rated torque	: 5.97 ft.lb	Approx. weight ³	: 98.6 lb
Locked rotor torque	: 300 %		
Breakdown torque	: 350 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.3991 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	70.9	72.5	77.0	78.5	Max. traction	: 84 lb
Power Factor	0.17	0.32	0.42	0.52	Max. compression	: 182 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
26.1	21.3	18.8	21.1	16.5	15.5	12.9

		Drive end	Non drive end
Bearing type	:	6207 ZZ	6206 ZZ
Sealing	:	V'Ring	Lip Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

USABLE @208V 5.09A SF 1.15 SFA 5.85A

This revision replaces and cancel the previous one, which must be eliminated.


- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Brake information

Voltage: 220-240 V

Brake Torque: 44.3 ft.lb

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	29/03/2024			Page 2 / 2	Revision