

# DATA SHEET

## Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Close Coupled Pump Single-Phase      Product code : 10360501

Frame	: 213JM	Locked rotor time	: 14s (cold) 8s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 33.4-30.3 A	Protection degree	: IP55
L. R. Amperes	: 254-230 A	Cooling method	: IC411 - TEFC
LRC	: 7.6x(Code H)	Mounting	: F-1
No load current	: 6.04-7.00 A	Rotation <sup>1</sup>	: CCW
Rated speed	: 3515 rpm	Starting method	: Direct On Line
Slip	: 2.36 %	Approx. weight <sup>3</sup>	: 144 lb
Rated torque	: 11.2 ft.lb		
Locked rotor torque	: 180 %		
Breakdown torque	: 270 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.4862 sq.ft.lb		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	80.9	82.0	83.0	84.0	Max. traction : 98 lb
Power Factor	0.65	0.88	0.93	0.94	Max. compression : 243 lb

	Drive end	Non drive end
Bearing type	: 6309 ZZ	6206 ZZ
Sealing	: V'Ring	V'Ring
Lubrication interval	: -	-
Lubricant amount	: -	-
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	26/03/2024				
				Page	Revision
				1 / 1	