

DATA SHEET


Three Phase Induction Motor - Squirrel Cage



Customer :																																																																											
Product line	: W40 High Efficiency Three-Phase		Product code :	15676856																																																																							
			Catalog # :	35030OP3OFP449TS-W40																																																																							
<table> <tr> <td>Frame</td><td>: 447/9TS</td> <td>Locked rotor time</td><td>: 68s (cold) 38s (hot)</td> </tr> <tr> <td>Output</td><td>: 350 HP (260 kW)</td><td>Temperature rise</td><td>: 70 K</td> </tr> <tr> <td>Poles</td><td>: 2</td><td>Duty cycle</td><td>: Cont.(S1)</td> </tr> <tr> <td>Frequency</td><td>: 50 Hz</td><td>Ambient temperature</td><td>: -20°C to +50°C</td> </tr> <tr> <td>Rated voltage</td><td>: 380 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td> </tr> <tr> <td>Rated current</td><td>: 462 A</td><td>Protection degree</td><td>: IP23</td> </tr> <tr> <td>L. R. Amperes</td><td>: 3049 A</td><td>Cooling method</td><td>: IC01 - ODP</td> </tr> <tr> <td>LRC</td><td>: 6.6x(Code G)</td><td>Mounting</td><td>: F-1</td> </tr> <tr> <td>No load current</td><td>: 68.0 A</td><td>Rotation¹</td><td>: Both (CW and CCW)</td> </tr> <tr> <td>Rated speed</td><td>: 2968 rpm</td><td>Starting method</td><td>: Direct On Line</td> </tr> <tr> <td>Slip</td><td>: 1.07 %</td><td>Approx. weight³</td><td>: 2194 lb</td> </tr> <tr> <td>Rated torque</td><td>: 619 ft.lb</td><td></td><td></td> </tr> <tr> <td>Locked rotor torque</td><td>: 160 %</td><td></td><td></td> </tr> <tr> <td>Breakdown torque</td><td>: 200 %</td><td></td><td></td> </tr> <tr> <td>Insulation class</td><td>: F</td><td></td><td></td> </tr> <tr> <td>Service factor</td><td>: 1.15</td><td></td><td></td> </tr> <tr> <td>Moment of inertia (J)</td><td>: 44.4 sq.ft.lb</td><td></td><td></td> </tr> <tr> <td>Design</td><td>: B</td><td></td><td></td> </tr> </table>				Frame	: 447/9TS	Locked rotor time	: 68s (cold) 38s (hot)	Output	: 350 HP (260 kW)	Temperature rise	: 70 K	Poles	: 2	Duty cycle	: Cont.(S1)	Frequency	: 50 Hz	Ambient temperature	: -20°C to +50°C	Rated voltage	: 380 V	Altitude	: 1000 m.a.s.l.	Rated current	: 462 A	Protection degree	: IP23	L. R. Amperes	: 3049 A	Cooling method	: IC01 - ODP	LRC	: 6.6x(Code G)	Mounting	: F-1	No load current	: 68.0 A	Rotation ¹	: Both (CW and CCW)	Rated speed	: 2968 rpm	Starting method	: Direct On Line	Slip	: 1.07 %	Approx. weight ³	: 2194 lb	Rated torque	: 619 ft.lb			Locked rotor torque	: 160 %			Breakdown torque	: 200 %			Insulation class	: F			Service factor	: 1.15			Moment of inertia (J)	: 44.4 sq.ft.lb			Design	: B		
Frame	: 447/9TS	Locked rotor time	: 68s (cold) 38s (hot)																																																																								
Output	: 350 HP (260 kW)	Temperature rise	: 70 K																																																																								
Poles	: 2	Duty cycle	: Cont.(S1)																																																																								
Frequency	: 50 Hz	Ambient temperature	: -20°C to +50°C																																																																								
Rated voltage	: 380 V	Altitude	: 1000 m.a.s.l.																																																																								
Rated current	: 462 A	Protection degree	: IP23																																																																								
L. R. Amperes	: 3049 A	Cooling method	: IC01 - ODP																																																																								
LRC	: 6.6x(Code G)	Mounting	: F-1																																																																								
No load current	: 68.0 A	Rotation ¹	: Both (CW and CCW)																																																																								
Rated speed	: 2968 rpm	Starting method	: Direct On Line																																																																								
Slip	: 1.07 %	Approx. weight ³	: 2194 lb																																																																								
Rated torque	: 619 ft.lb																																																																										
Locked rotor torque	: 160 %																																																																										
Breakdown torque	: 200 %																																																																										
Insulation class	: F																																																																										
Service factor	: 1.15																																																																										
Moment of inertia (J)	: 44.4 sq.ft.lb																																																																										
Design	: B																																																																										
Output	25%	50%	75%	100%																																																																							
Efficiency (%)	94.7	94.4	95.0	95.0																																																																							
	94.1	95.0	95.0	95.0																																																																							
Power Factor	0.78	0.74	0.89	0.87																																																																							
	0.71	0.86	0.89	0.90																																																																							
<table> <tr> <td>Bearing type</td><td>:</td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr> <td></td><td></td><td>6314 C3</td><td colspan="2">6314 C3</td></tr> <tr> <td>Sealing</td><td>:</td><td>Without Bearing Seal</td><td colspan="2">Without Bearing Seal</td></tr> <tr> <td>Lubrication interval</td><td>:</td><td>4500 h</td><td colspan="2">4500 h</td></tr> <tr> <td>Lubricant amount</td><td>:</td><td>27 g</td><td colspan="2" rowspan="5">27 g</td></tr> <tr> <td>Lubricant type</td><td>:</td><td colspan="3" rowspan="4">Mobil Polyrex EM</td></tr> </table>					Bearing type	:	Drive end	Non drive end				6314 C3	6314 C3		Sealing	:	Without Bearing Seal	Without Bearing Seal		Lubrication interval	:	4500 h	4500 h		Lubricant amount	:	27 g	27 g		Lubricant type	:	Mobil Polyrex EM																																											
Bearing type	:	Drive end	Non drive end																																																																								
		6314 C3	6314 C3																																																																								
Sealing	:	Without Bearing Seal	Without Bearing Seal																																																																								
Lubrication interval	:	4500 h	4500 h																																																																								
Lubricant amount	:	27 g	27 g																																																																								
Lubricant type	:	Mobil Polyrex EM																																																																									
Notes:																																																																											
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>																																																																											
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																											
Rev.	Changes Summary			Performed																																																																							
				Checked																																																																							
Performed by																																																																											
Checked by																																																																											
Date	26/03/2024																																																																										
		Page	Revision																																																																								
		1 / 2																																																																									
Customer :																																																																											
Product line	: W40 High Efficiency Three-Phase		Product code :	15676856																																																																							
			Catalog # :	35030OP3OFP449TS-W40																																																																							
<table> <tr> <td>Frame</td><td>: 447/9TS</td><td>Locked rotor time</td><td>: 68s (cold) 38s (hot)</td></tr> <tr> <td>Output</td><td>: 350 HP (260 kW)</td><td>Temperature rise</td><td>: 70 K</td></tr> <tr> <td>Poles</td><td>: 2</td><td>Duty cycle</td><td>: Cont.(S1)</td></tr> <tr> <td>Frequency</td><td>: 50 Hz</td><td>Ambient temperature</td><td>: -20°C to +50°C</td></tr> <tr> <td>Rated voltage</td><td>: 380 V</td><td>Altitude</td><td>: 1000 m.a.s.l.</td></tr> <tr> <td>Rated current</td><td>: 462 A</td><td>Protection degree</td><td>: IP23</td></tr> <tr> <td>L. R. Amperes</td><td>: 3049 A</td><td>Cooling method</td><td>: IC01 - ODP</td></tr> <tr> <td>LRC</td><td>: 6.6x(Code G)</td><td>Mounting</td><td>: F-1</td></tr> <tr> <td>No load current</td><td>: 68.0 A</td><td>Rotation¹</td><td>: Both (CW and CCW)</td></tr> <tr> <td>Rated speed</td><td>: 2968 rpm</td><td>Starting method</td><td>: Direct On Line</td></tr> <tr> <td>Slip</td><td>: 1.07 %</td><td>Approx. weight³</td><td>: 2194 lb</td></tr> <tr> <td>Rated torque</td><td>: 619 ft.lb</td><td></td><td></td></tr> <tr> <td>Locked rotor torque</td><td>: 160 %</td><td></td><td></td></tr> <tr> <td>Breakdown torque</td><td>: 200 %</td><td></td><td></td></tr> <tr> <td>Insulation class</td><td>: F</td><td></td><td></td></tr> <tr> <td>Service factor</td><td>: 1.15</td><td></td><td></td></tr> <tr> <td>Moment of inertia (J)</td><td>: 44.4 sq.ft.lb</td><td></td><td></td></tr> <tr> <td>Design</td><td>: B</td><td></td><td></td></tr> </table>				Frame	: 447/9TS	Locked rotor time	: 68s (cold) 38s (hot)	Output	: 350 HP (260 kW)	Temperature rise	: 70 K	Poles	: 2	Duty cycle	: Cont.(S1)	Frequency	: 50 Hz	Ambient temperature	: -20°C to +50°C	Rated voltage	: 380 V	Altitude	: 1000 m.a.s.l.	Rated current	: 462 A	Protection degree	: IP23	L. R. Amperes	: 3049 A	Cooling method	: IC01 - ODP	LRC	: 6.6x(Code G)	Mounting	: F-1	No load current	: 68.0 A	Rotation ¹	: Both (CW and CCW)	Rated speed	: 2968 rpm	Starting method	: Direct On Line	Slip	: 1.07 %	Approx. weight ³	: 2194 lb	Rated torque	: 619 ft.lb			Locked rotor torque	: 160 %			Breakdown torque	: 200 %			Insulation class	: F			Service factor	: 1.15			Moment of inertia (J)	: 44.4 sq.ft.lb			Design	: B		
Frame	: 447/9TS	Locked rotor time	: 68s (cold) 38s (hot)																																																																								
Output	: 350 HP (260 kW)	Temperature rise	: 70 K																																																																								
Poles	: 2	Duty cycle	: Cont.(S1)																																																																								
Frequency	: 50 Hz	Ambient temperature	: -20°C to +50°C																																																																								
Rated voltage	: 380 V	Altitude	: 1000 m.a.s.l.																																																																								
Rated current	: 462 A	Protection degree	: IP23																																																																								
L. R. Amperes	: 3049 A	Cooling method	: IC01 - ODP																																																																								
LRC	: 6.6x(Code G)	Mounting	: F-1																																																																								
No load current	: 68.0 A	Rotation ¹	: Both (CW and CCW)																																																																								
Rated speed	: 2968 rpm	Starting method	: Direct On Line																																																																								
Slip	: 1.07 %	Approx. weight ³	: 2194 lb																																																																								
Rated torque	: 619 ft.lb																																																																										
Locked rotor torque	: 160 %																																																																										
Breakdown torque	: 200 %																																																																										
Insulation class	: F																																																																										
Service factor	: 1.15																																																																										
Moment of inertia (J)	: 44.4 sq.ft.lb																																																																										
Design	: B																																																																										
Output	25%	50%	75%	100%																																																																							
Efficiency (%)	94.7	94.4	95.0	95.0																																																																							
	94.1	95.0	95.0	95.0																																																																							
Power Factor	0.78	0.74	0.89	0.87																																																																							
	0.71	0.86	0.89	0.90																																																																							
<table> <tr> <td>Bearing type</td><td>:</td><td>Drive end</td><td colspan="2">Non drive end</td></tr> <tr> <td></td><td></td><td>6314 C3</td><td colspan="2">6314 C3</td></tr> <tr> <td>Sealing</td><td>:</td><td>Without Bearing Seal</td><td colspan="2">Without Bearing Seal</td></tr> <tr> <td>Lubrication interval</td><td>:</td><td>4500 h</td><td colspan="2">4500 h</td></tr> <tr> <td>Lubricant amount</td><td>:</td><td>27 g</td><td colspan="2" rowspan="5">27 g</td></tr> <tr> <td>Lubricant type</td><td>:</td><td colspan="3" rowspan="4">Mobil Polyrex EM</td></tr> </table>					Bearing type	:	Drive end	Non drive end				6314 C3	6314 C3		Sealing	:	Without Bearing Seal	Without Bearing Seal		Lubrication interval	:	4500 h	4500 h		Lubricant amount	:	27 g	27 g		Lubricant type	:	Mobil Polyrex EM																																											
Bearing type	:	Drive end	Non drive end																																																																								
		6314 C3	6314 C3																																																																								
Sealing	:	Without Bearing Seal	Without Bearing Seal																																																																								
Lubrication interval	:	4500 h	4500 h																																																																								
Lubricant amount	:	27 g	27 g																																																																								
Lubricant type	:	Mobil Polyrex EM																																																																									
Notes:																																																																											
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>																																																																											
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																																																																											
Rev.	Changes Summary			Performed																																																																							
				Checked																																																																							
Performed by																																																																											
Checked by																																																																											
Date	26/03/2024																																																																										
		Page	Revision																																																																								
		1 / 2																																																																									

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.

Changes Summary

Performed

Checked

Date

Performed by

Checked by

Date

26/03/2024

Page

2 / 2

Revision