## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer	:				
Product line : Close Coupled Pump NEMA Premium Efficiency Three-Phase			m Product code : Catalog # :	11064401 02536OT3E256JM	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia Design	: : : : : : : : : : : : : : : : : : :	256JM 25 HP (18.5 kW) 2 60 Hz 230/460 V 59.6/29.8 A 387/194 A 6.5x(Code G) 22.0/11.0 A 3530 rpm 1.94 % 37.2 ft.lb 200 % 260 % F 1.15 1.08 sq.ft.lb B		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 16s (cold) 9s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP23 : IC01 - ODP : F-1 : Both (CW and CCW) : 67.0 dB(A) : Direct On Line : 242 lb
Output	25% 50%		100%	Foundation loads	
Efficiency (%) Power Factor	84.2 85.5 86.8 88.2 87.0 88.8 88.6 89.8 0.47 0.49 0.73 0.44 0.39 0.68	3 0.72 0.82 0.82 8 0.63 0.79 0.75 8 0.74 0.86 0.83	91.9 91.9 89.5 90.9 91.0 0.85 0.87 0.84 0.82	Max. traction  Max. compression	: 525 lb : 767 lb
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type Notes:	: : al : :	Drive 6309 Without Be 2000 13	Z C3 aring Seal 00 h g	Non drive end 6209 Z C3 Without Bearing Se 20000 h 9 g bil Polyrex EM	eal

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

, , , , , , , , , , , , , , , , , , , ,					
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024	1		1/1	