DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer	:				
Product line		upled Pump NEN Three-Phase	MA Premiur	m Product code : Catalog # :	11263081 10018OT3E404JP
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia Design	: 1 : 4 : 6 : 2 : 1 : 8 : 1 : 1 : 2 : 4 : 2 : 4 : 5 : 1 : 2 : 2 : 1 : 1 : 1 : 1 : 1 : 1 : 1 : 1 : 1 : 1	60 Hz 230/460 V 226/113 A 1514/757 A 6.7x(Code G) 34.0/42.0 A 1780 rpm 1.11 % 295 ft.lb 229 % 270 % = 1.15		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 18s (cold) 10s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP23 : IC01 - ODP : F-1 : Both (CW and CCW) : 69.0 dB(A) : Direct On Line : 996 lb
Output	25% 50%	75%	100%	Foundation loads	
Efficiency (%) Power Factor	91.0 90.8 91.9 93.7 93.7 93.9 93.7 93.9 0.49 0.48 0.77	0.75 0.84 0.85	94.6 94.6 94.1 94.1 94.1 0.87 0.89	Max. traction Max. compression	: 2694 lb : 3690 lb
		0.66 0.83 0.79 0.80 0.88 0.87 0.85			
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type	: : : : :	Drive e 6314 Without Bea 2000 27	C3 aring Seal 0 h g	Non drive end 6314 C3 Without Bearing Se 20000 h 27 g bil Polyrex EM	al
Notes:					

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

(1)/11/100/00110					
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by		1		Page	Revision
Date	28/03/2024			1/1	