## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer	:				
Product line	: Close Cou Efficiency Tl	pled Pump NEI hree-Phase	MA Premiui	m Product code :  Catalog # :	11289896 05036OT3G324JP
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia Design	: 50 : 2 : 60 : 46 : 59 : 37 : 6. : 20 : 38 : 0. : 73 : e : 22 : F : F	24JP 0 HP (37 kW) 0 Hz 60 V 9.1 A 78 A 4x(Code G) 0.5 A 665 rpm 97 % 3.7 ft.lb 29 % 40 % 15 83 sq.ft.lb		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 50s (cold) 28s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP23 : IC01 - ODP : F-1 : Both (CW and CCW) : 74.0 dB(A) : Direct On Line : 491 lb
Output	25% 50%	75%	100%	Foundation loads	
Efficiency (%)	92.2 88.0 92.4 8 87.9 88.6 89.6 9 90.1 90.1 91.0 9 90.1 91.0	90.0 91.6 92.0	93.3 93.4	Max. traction	: 537 lb
Power Factor	0.49 0.50 0.74 0 0.44 0.40 0.68 0 0.56 0.50 0.78 0 0.45 0.69	0.64 0.77 0.73	0.81 0.79	Max. compression	: 1029 lb
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type Notes:	: : al : : :	Drive 6 6312 Without Be 1965 21	Z C3 aring Seal 88 h	Non drive end 6212 Z C3 Without Bearing Se 20000 h 13 g bil Polyrex EM	al

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

, , , , , , , , , , , , , , , , , , , ,					
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	29/03/2024	1		1/1	