

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Jet Pump - J type Standard  
Efficiency Three-Phase

Product code : 14410881

Catalog # : .7536ES3HJPRW56J-S

Frame : W56J  
Output : 0.75 HP (0.55 kW)  
Poles : 2  
Frequency : 60 Hz  
Rated voltage : 575 V  
Rated current : 0.928 A  
L. R. Amperes : 6.40 A  
LRC : 6.9x(Code K)  
No load current : 0.542 A  
Rated speed : 3400 rpm  
Slip : 5.56 %  
Rated torque : 1.16 ft.lb  
Locked rotor torque : 300 %  
Breakdown torque : 300 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 0.0168 sq.ft.lb

Locked rotor time : 25s (cold) 14s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-1  
Rotation<sup>1</sup> : CCW  
Noise level<sup>2</sup> : 65.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 16.1 lb

Output	25%	50%	75%	100%
Efficiency (%)	64.0	66.0	70.0	72.0
Power Factor	0.38	0.64	0.76	0.83

Foundation loads  
Max. traction : 26 lb  
Max. compression : 42 lb

	Drive end	Non drive end
Bearing type	6203 2RS	6202 2RS
Sealing	V'Ring	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	27/03/2024			