

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 NEMA Premium Efficiency Three-Phase

Product code : 14112411

Catalog # : 35036OT3G449TSC-RFW4

Frame : 447/9TSC
Output : 350 HP (260 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 460 V
Rated current : 384 A
L. R. Amperes : 2496 A
LRC : 6.5x(Code G)
No load current : 88.0 A
Rated speed : 3565 rpm
Slip : 0.97 %
Rated torque : 516 ft.lb
Locked rotor torque : 170 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 35.7 sq.ft.lb
Design : A

Locked rotor time : 25s (cold) 14s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 87.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 2019 lb

Output	25%		50%		75%		100%	
Efficiency (%)	94.9	93.4	95.0	94.4	95.4	94.8	95.4	95.8
	93.7	93.7	94.5	94.5	95.1	95.1	95.8	95.8
	94.5	94.9	95.0	95.0	94.5	95.0	95.0	95.0
	94.9		95.0		95.0		95.0	
Power Factor	0.61	0.61	0.83	0.81	0.88	0.88	0.89	0.90
	0.58	0.55	0.79	0.78	0.87	0.86	0.89	0.89
	0.65	0.62	0.84	0.83	0.89	0.88	0.90	0.89
	0.60		0.82		0.88		0.89	

Foundation loads
Max. traction : 2963 lb
Max. compression : 4982 lb

	Drive end	Non drive end
Bearing type :	6314 C4	6314 C4
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	14418 h	14418 h
Lubricant amount :	27 g	27 g
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			
			Page	Revision
			1 / 2	

Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	26/03/2024				