

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 JP Pump High Efficiency Three-Phase      Product code : 14829216  
Catalog # : 04036OP3HFP286JPV-W4

Frame	: 284/6JP	Locked rotor time	: 18s (cold) 10s (hot)
Output	: 40 HP (30 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 37.8 A	Protection degree	: IP23
L. R. Amperes	: 230 A	Cooling method	: IC01 - ODP
LRC	: 6.1x(Code G)	Mounting	: W-6
No load current	: 10.4 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3540 rpm	Starting method	: Direct On Line
Slip	: 1.67 %	Approx. weight <sup>3</sup>	: 373 lb
Rated torque	: 59.3 ft.lb		
Locked rotor torque	: 220 %		
Breakdown torque	: 220 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 1.91 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	90.8	91.0	91.7	91.7	Max. traction
Power Factor	0.54	0.77	0.85	0.87	Max. compression

	Drive end	Non drive end
Bearing type	: 6311 Z C3	: 6211 Z C3
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: 11517 h	: 14226 h
Lubricant amount	: 18 g	: 11 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	30/03/2024			

Page 1 / 1  
Revision