

Three Phase Induction Motor - Squirrel Cage



Product line : W40 JP Pump High Efficiency Three-Phase Product code : 14829574
Catalog # : 07536OP3EFP364JPV-W4

Frame	: 364/5JP	Locked rotor time	: 46s (cold) 26s (hot)
Output	: 75 HP (55 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 171/85.3 A	Protection degree	: IP23
L. R. Amperes	: 990/495 A	Cooling method	: IC01 - ODP
LRC	: 5.8x(Code F)	Mounting	: W-6
No load current	: 44.0/22.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3550 rpm	Starting method	: Direct On Line
Slip	: 1.39 %	Approx. weight ³	: 701 lb
Rated torque	: 111 ft.lb		
Locked rotor torque	: 160 %		
Breakdown torque	: 210 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 5.60 sq.ft.lb		
Design	: B		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	90.3	91.1	91.0	91.5	92.4	91.7	93.0	91.9	Max. traction	: 566 lb
	91.5	91.3	91.7	91.7	92.4	92.4	92.4	92.6		
Power Factor	0.57	0.63	0.80	0.84	0.85	0.87	0.87	0.88	Max. compression	: 1267 lb
	0.58	0.54	0.80	0.77	0.86	0.85	0.87	0.87		

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type	6314 C3	6212 Z C3
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	7209 h	12143 h
Lubricant amount	27 g	13 g
Lubricant type	Mobil Polyrex EM	

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				1 / 1	
Date	30/03/2024				