

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : ODP High Efficiency Three-Phase

Product code : 12722043
Catalog # : 20036OP3HFP444TS

Frame	: 444/5TS	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 200 HP (150 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 183 A	Protection degree	: IP23
L. R. Amperes	: 1154 A	Cooling method	: IC01 - ODP
LRC	: 6.3x(Code G)	Mounting	: F-1
No load current	: 44.8 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3570 rpm	Noise level ²	: 85.0 dB(A)
Slip	: 0.83 %	Starting method	: Direct On Line
Rated torque	: 294 ft.lb	Approx. weight ³	: 1378 lb
Locked rotor torque	: 190 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 26.8 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	92.8	93.0	94.5	94.5	Max. traction	: 1272 lb
Power Factor	0.58	0.80	0.85	0.87	Max. compression	: 2649 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6314 C3
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	14418 h	14418 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1 Revision		
Checked by				
Date	30/03/2024			