# **DATA SHEET**

### Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W60 Three-Phase Product code : 16166655

Frame : 5010/11 Locked rotor time : 41s (cold) 23s (hot)

Output : 350 HP (260 kW) Temperature rise : 80 K
Poles : 2 Duty cycle : Cont.(S1)
Frequency : 60 Hz

Frequency : 60 Hz Ambient temperature : -20°C to +40°C Rated voltage : 4160 V Altitude : 1000 m.a.s.l. Rated current : 43.2 A Protection degree : IP24

: F-1 Mounting L. R. Amperes : 281 A Rotation<sup>1</sup> **LRC** : 6.5x(Code G) : CW No load current : 11.2 A Noise level<sup>2</sup> : 80.0 dB(A) Rated speed : 3568 rpm Starting method : Direct On Line

Slip : 0.89 % Approx. weight³ : 3927 lb

Rated torque : 515 ft.lb

Locked rotor torque : 240 %

Moment of inertia (J) : 60.2 sq.ft.lb

Output 25% 50% 75% 100% Foundation loads

 Efficiency (%)
 93.8
 94.0
 95.0
 95.0
 Max. traction

 Power Factor
 0.59
 0.84
 0.86
 0.88
 Max. compression

: F

: 1.00

Drive end<br/>Bearing typeNon drive end<br/>6218 C4Sealing: 6218 C46218 C4Without Bearing SealWithout Bearing Seal

Lubrication interval : 12045 h 12045 h

Lubricant amount : 24 g 24 g Lubricant type : Mobil Polyrex EM

Notes:

Insulation class

Service factor

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev.         | Changes Summary |  | Performed | Checked | Date     |
|--------------|-----------------|--|-----------|---------|----------|
|              |                 |  |           |         |          |
| Performed by |                 |  |           |         |          |
| Checked by   |                 |  |           | Page    | Revision |
| Date         | 27/03/2024      |  |           | 1/2     |          |

# **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



| Customer |  |
|----------|--|
|          |  |

| Thermal | protection |
|---------|------------|
|---------|------------|

| ID | Application | Туре            | Quantity    | Sensing Temperature |
|----|-------------|-----------------|-------------|---------------------|
| 1  | Winding     | PT100 - 3 wires | 2 x Phase   | -                   |
| 2  | DE bearing  | PT100 - 3 wires | 1 x Bearing | -                   |
| 3  | NDE bearing | PT100 - 3 wires | 1 x Bearing | -                   |

#### Space heater information

Voltage: 110-127/200-240 V

| Rev.         | Changes Summary Performed |  | Performed | Checked | Date     |
|--------------|---------------------------|--|-----------|---------|----------|
|              |                           |  |           |         |          |
| Performed by |                           |  |           |         |          |
| Checked by   |                           |  |           | Page    | Revision |
| Date         | 27/03/2024                |  |           | 2/2     |          |