



MATERIALS:	
HOUSING:	GLASS REINFORCED THERMOPLASTIC NICK
	NICKEL PLATED BRASS HARDWARE
SCREWS:	NICKEL PLATED BRASS
WIRE:	8 - 14 AWG
AMBIENT TEMP. LIMIT:	(-40 C...+125 C)
RATINGS:	UL / CSA - 600V, 10A. EN 1000V / 8k V/3, 40A

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.

UNLESS OTHERWISE SPECIFIED:  DIMENSIONS ARE IN INCHES AND [MM]		DRAWN BY	DCG	MENCOM CORPORATION	
		DRAWN DATE	07/11/2019		
		CHECKED BY	GO		
		CHECK DATE	07/11/2019		
				TITLE:	
				2 PL MIXO FEM AXL SCREW INSERT 40AMP 8-14AWG	
				SIZE	DWG. NO.
				<b>B</b>	CX-02-4AF
				SCALE: 1:1	WEIGHT:
				SHEET 1 OF 1	

REV  
**B**