



FEMALE USB
TYPE A

FILLER PLUG

CHINESE RECEPTACLE
10A, 250V, CCC CERTIFICATION

MALE USB
TYPE A

PANEL CUTOUT

PART NUMBER	LENGTH "L"
DCH1-RJ45-USB-03-32	3 FEET
DCH1-RJ45-USB-06-32	6 FEET
DCH1-RJ45-USB-10-32	10 FEET

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS			
VOLTS:		250V	
AMPS:		10A	
NEMA/UL EN 60529:		4, 4X, 12 IP65	
MOUNTING SCREW SIZE:		M4 (8-32) (304 or 316SS for 4X)	
MOUNTING SCREW TORQUE:		1.2~1.8N-m (0.9~1.3 Lb-Ft)	
INCOMING POWER WIRE SIZE:		0.5 ~ 4.0 sq mm / 20-12AWG	
WIRE STRIP LENGTH:		10 ~ 11 mm	

HOUSING MATERIALS	
BODY:	EPOXY COATED DIE CAST ALUMINUM
GASKET:	THERMOPLASTIC ELASTOMER
HANDLE:	POLYAMIDE
LEVERS:	STAINLESS STEEL

OPERATING TEMPERATURE: (-5°C / +50° C (+23° F / +122° F))

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
AND [MM]

DRAWN BY	DCG
DRAWN DATE	06/15/2021
CHECKED BY	DCG
CHECK DATE	06/15/2021

COMMENTS:

MENCOM CORPORATION

TITLE:
CHINA RCPT; RJ45; USB PN; 32

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

MATERIAL

FINISH

DO NOT SCALE DRAWING

SIZE	DWG. NO.	REV
B	DCH1-RJ45-USB-ZZ-32	C
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1