

1

D

С

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth

o a surface tha	at is clean, flat ar	id smooth.			
	PIC RATING	S/SPEC	IFICATIONS		
		12	5V		
		15	A		
		10	kA		
IL EN 60529:			4, 4X, 12 IP65		
NG SCREW SIZE:			M4 (8-32) (304 or 316SS for 4X)		
NG SCREW TORQUE:			1.2~1.8N-m (0.9~1.3 Lb-Ft)		
NG POWER WIRE SIZE:			0.5 ~ 4.0 sq mm / 20-12AWG		
TRIP LENGTH:			10 ~ 11 mm		
07/12/2021	MENCOM CORPORATION				
DCG	TITLE:				
07/13/2021				00	A
	DPT; 2 RJ45; 32				
:					
SIZE DWG. NO.					
	B DPT-2RJ45-32 C				
	SCALE: 2:3	CALE: 2:3 WEIGHT: SHEET 1 OF 1			
	į	i			

1