



RCBO 16 AMP 230V, 30mA trip

- 1. DOWNSTREAM OUTLETS CAN ALSO BE PROTECTED
- 2. NO RESET REQUIRED AFTER POWER FAILURE (LATCHED RCD)
- 3. OPERATIONAL TEMPERATURE -5°C TO +40°C
- 4. TERMINAL TORQUE = 0.08 Nm NEWTON METERS
- 5. NOTE: CANNOT BE USE ON 125 VOLT (PHASE TO NEUTRAL) OR 250 VOLT (125V / 125V PHASE TO PHASE) U.S. TYPE ELECTRICAL CIRCUITS.
- 6. NOT SUITABLE FOR APPLIANCES THAT HAVE INTERNAL FILTER CONDENSERS WITH CONNECTIONS BETWEEN PHASE/NEUTRAL, PHASE/GROUND, NEUTRAL GROUND.
- 7. THIS PRODUCT IS FOR USE IN CONJUNCTION WITH A MAIN PROTECTIVE DEVICE. IT IS NOT SUITABLE FOR PROTECTING DEVICES WITH A CONNECTION TO EARTH. THIS PRODUCT DOES NOT OPERATE WITH FERROMAGNETIC TRANSFORMERS.

3A RESET ALLOWS FOR ADDITIONAL OVERLOAD PROTECTION

MULTI-CONFIGURATION OUTLET ACCEPTS NEMA 1-15P, 5-15P, 6-15P, 5-20P, 6-20P, & UK1-13P, UK3-5P, JA1-15P, EU1-16P (NON-GROUNDING), AU1-10P, AU2-15P, CH1-10P, EUROPLUG AND AR1-10P TYPE PLUGS

9 PIN D-SUB CONFIGURED MALE EXTERIOR/MALE INTERIOR

PANEL CUTOUT

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT. 6 JACK	CAT. 6 JACK

MOUNTING KIT ORDERED SEPARATELY CONTAINS M6x1 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M6 NUT
P/N: D-PIC48-MT

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

HOUSING MATERIALS	
BODY:	EPOXY COATED DIE CAST ALUMINUM
GASKET:	THERMOPLASTIC ELASTOMER
HANDLE:	STAINLESS STEEL

ED S N WASHER, ND M6 NUT		UNLESS OTHERWISE SPECIFIED:
		DIMENSIONS ARE IN INCHES AND [MM]
		MATERIAL
		FINISH
		DO NOT SCALE DRAWING

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS	
VOLTS:	230V
AMPS:	3A
SCCR:	0.2kA
NEMA/UL EN 60529:	4, 4X, 12 IP65
MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)
INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
WIRE STRIP LENGTH:	10 ~ 11 mm

MENCOM CORPORATION

TITLE:
UN RCPT;GFI BKR;DB9MM;RJ;3A;48

SIZE B	DWG. NO. DUNGF-DB9M-RJ45-R-48	REV F
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1