

- 5 A modular SSR, 1 NO AC output**
- 17.5 mm housing
 - 60 to 240 V AC output (with back to back SCR)
 - 5 kV (1.2/50 µs) insulation between Input and Output
 - Zero-crossing and random switch-on versions available
 - High switching speed
 - High endurance
 - Silent switching
 - Spark and bounce-free switching
 - Low control power
 - 3-phase general purpose
 - 35 mm rail (EN 60715) mount

77.01

Screw terminal



* See L77-3 diagram page 11

** See L77-1 and L77-2 diagrams page 10

For outline drawing see page 14

Output specification

Output configuration	1 NO (SPST-NO)	1 NO (SPST-NO)
Rated current I_N /Max. peak current* (10 ms) A	5/300*	5/300*
Rated voltage V AC (50/60 Hz)	230	230
Switching voltage range V AC (50/60 Hz)	48...265	48...265
Repetitive peak off-state voltage V_{pk}	800	800
Rated load AC7a ($\cos \varphi = 0.8$) A	5	5
Rated load AC15 A	5	3
Single phase motor rating (230V AC) kW	—	0.1
Nominal lamp rating:		
230 V incandescent/halogen W	1000	800
fluorescent tubes with electronic ballast W	1000	800
fluorescent tubes with electromechanical ballast W	1000	800
CFL W	800	400
230 V LED W	800	400
LV halogen or LED with electronic ballast W	800	400
LV halogen or LED with electromechanical ballast W	1000	800
Minimum switching current @ 230 V mA	100	100
Typical "OFF-state" leakage current @ 230 V mA	0.5	3.5
Max "ON-state" voltage drop @ 25 °C and 5 A/100 mA V	0.85/1.5	0.85/1.5
Power loss @ 5 A W	4	4

Input specification

Nominal voltage (U_N)	V AC (50/60 Hz)	24	230	24	230
	V DC	12...24	—	12...24	—
Rated power	VA (50 Hz)/W	0.6/0.5	3.6/0.3	0.6/0.5	3.6/0.3
Operating range	V AC (50/60 Hz)	16...32	90...265	16...32	90...265
	V DC	9.8...32	—	9.8...32	—
Must drop-out voltage	V AC (50/60 Hz)/DC	2.4	24	2.4	24

Technical data

Electrical life	cycles	$10 \cdot 10^6$	$10 \cdot 10^6$
Operate/release time	ms	20/12	9/8
Insulation between input and output (1.2/50 µs)	kV	5	5
Ambient temperature	°C	-20...+70**	-20...+70**
Protection category		IP 20	IP 20
Approvals (according to type)			

77.01.x.xxx.8050




77.01.x.xxx.8051



Zero-crossing switch-on

Suggested applications:

- Lamp inrush current reduction (CFL - Compact Fluorescent energy-saving Lamps and similar)
- Heater control
- Solenoid, contactor driver




Simplified circuit diagram

Random switch-on

Suggested applications:

- Finer control requiring short operate time (specially motor control)
- AC Input phase different from AC Output phase



Simplified circuit diagram

7 - 15 A modular SSR, 1 NO DC output

- 17.5 mm housing
- 2 versions, for 24 and 125 V DC mosfet output
- 4 kV (1.2/50 µs) insulation between Input and Output
- Short circuit protection
- High switching speed
- High endurance
- Silent switching
- Spark and bounce-free switching
- Low control power
- Suitable for railway applications
- 35 mm rail (EN 60715) mount

77.01

Screw terminal



* See L77-12 and L77-13 diagrams page 10

D

For outline drawing see page 14

Output specification

		1 NO (SPST-NO)	1 NO (SPST-NO)
Rated current I_N /Max. peak current (10 ms)	A	15/160	7/60
Rated voltage	V DC	24	125
Switching voltage range	V DC	16...32	43...140
Rated load DC13	A	5	2.5
DC motor rating	kW	0.2	—
Minimum switching current	mA	100	50
Typical "OFF-state" leakage current	mA	3	6
Max "ON-state" voltage drop @ 25 °C and I_N	V	0.06	0.2
Power loss @ I_N	W	1	1.5

Input specification

Nominal voltage (U_N)	V DC	6...24	6...24
Rated power	W	0.5	0.5
Operating range	V DC	4...36	4...36
Must drop-out voltage	V DC	3	3

Technical data


Electrical life	cycles	$10 \cdot 10^6$	$10 \cdot 10^6$
Operate/release time	ms	0.05/2	0.05/2
Insulation between input and output (1.2/50 µs)	kV	4	4
Ambient temperature	°C	-20...+70*	-20...+70*
Protection category		IP 20	IP 20

Approvals (according to type)

77.01.9.024.9024


**24 V DC output switching
15 A rated**
**Applications in Energy,
Automation and Machines:**

- Control of electric, pneumatic and hydraulic electromagnetic valves
- Direct control of loads such as motors and electromagnets


77.01.9.024.9125

**110...125 V DC output
switching
7 A rated**
**Applications in Energy,
Automation and Machines:**

- Control of electric, pneumatic and hydraulic electromagnetic valves
- Direct control of loads such as motors and electromagnets



15 A modular SSR, 1 NO output

- 22.5 mm housing, heat-sink + plastic cover
- 24 to 277 V AC output (with triac)
- 6 kV (1.2/50 µs) insulation between Input and Output
- Zero-crossing and random switch-on versions available
- High switching speed
- High endurance
- Silent switching
- Spark and bounce-free switching
- Low control power
- 3-phase general purpose
- "Relay-style" terminal arrangement (input and output terminals on opposite sides)
- 35 mm rail (EN 60715) mount

77.11

Screw terminal



* See L77-7 diagram page 11

** See L77-6 diagrams page 10

For outline drawing see page 14

Output specification

Output configuration	1 NO (SPST-NO)	1 NO (SPST-NO)
Rated current I_N /Max. peak current* (10 ms) A	15/400*	15/400*
Rated voltage V AC (50/60 Hz)	230	230
Switching voltage range V AC (50/60 Hz)	19...305	19...305
Repetitive peak off-state voltage V_{pk}	800	800
Rated load AC7a ($\cos \varphi = 0.8$, @ 25 °C) A	20	20
Rated load AC15 A	15	15
Single phase motor rating (230 V AC) kW	—	0.75
Nominal lamp rating:		
230 V incandescent/halogen W	4000	2500
fluorescent tubes with electronic ballast W	4000	2500
fluorescent tubes with electromechanical ballast W	2000	1000
CFL W	3000	1500
230 V LED W	3000	1500
LV halogen or LED with electronic ballast W	3000	1500
LV halogen or LED with electromechanical ballast W	3000	1500
Minimum switching current @ 250 V mA	100	100
Typical "OFF-state" leakage current @ 250 V mA	1	1
Max "ON-state" voltage drop @ 25 °C and 15 A V	1.55	1.55
Power loss @ 15 A W	14	14

Input specification

Nominal voltage (U_N)	V AC (50/60 Hz)	—	230	—	230
	V DC	24	—	24	—
Rated power	VA (50 Hz)/W	0.4	7.5/0.9	0.4	7.5/0.9
Operating range	V AC (50/60 Hz)	—	40...305	—	40...305
	V DC	4...32	—	4...32	—
Must drop-out voltage	V AC (50/60 Hz)/DC	—/2	6/—	—/2	6/—

Technical data


Electrical life	cycles	$10 \cdot 10^6$		$10 \cdot 10^6$	
Operate/release time	ms	< 10/< 10	< 10/< 30	< 1/< 10	< 2/< 25
Insulation between input and output (1.2/50 µs)	kV	6	6	-20...+80**	-20...+80**
Ambient temperature	°C	IP 20	IP 20	IP 20	IP 20
Protection category					
Approvals (according to type)					

77.11.x.xxx.8250



Zero-crossing switch-on
Suggested applications:

- Lamp inrush current reduction (CFL - Compact Fluorescent energy-saving Lamps and similar)
- Heater control
- Solenoid, contactor driver




77.11.x.xxx.8251



Random switch-on
Suggested applications:

- Fine controls involving shorter time (especially motor control)



30 A modular SSR, 1 NO output

- 22.5 mm housing, heat-sink + plastic cover
- 60 to 440 V AC output (with back to back SCR)
- 6 kV (1.2/50 µs) insulation between Input and Output
- Zero-crossing and random switch-on versions available
- High switching speed
- High endurance
- Silent switching
- Spark and bounce-free switching
- Low control power
- 3-phase general purpose
- "Relay-style" terminal arrangement (input and output terminals on opposite sides)
- 35 mm rail (EN 60715) mount

77.31

Screw terminal



* See L77-5 diagram page 11

** See L77-4 diagrams page 10

D


For outline drawing see page 14

Output specification


Output configuration	1 NO (SPST-NO)		1 NO (SPST-NO)	
Rated current I _N /Max. peak current* (10 ms) A		30/520*		30/520*
Rated voltage V AC (50/60 Hz)		400		400
Switching voltage range V AC (50/60 Hz)		48...480		48...480
Repetitive peak off-state voltage V _{pk}		1100		1100
Rated load AC7a (cos φ = 0.8) A		30		30
Rated load AC15 A		20		20
Single phase motor rating (230 V AC) kW		—		1.5
Nominal lamp rating:				
230 V incandescent/halogen W		6000		4500
fluorescent tubes with electronic ballast W		6000		4000
fluorescent tubes with electromechanical ballast W		3000		1800
CFL W		4000		2500
230 V LED W		4000		2500
LV halogen or LED with electronic ballast W		4000		2500
LV halogen or LED with electromechanical ballast W		4000		2500
Minimum switching current @ 400 V mA		300		300
Typical "OFF-state" leakage current @ 400 V mA		1		1
Max "ON-state" voltage drop @ 25 °C and 30 A V		0.85		0.85
Power loss @ 30 A W		16		16
Input specification				
Nominal voltage (U _N) V AC (50/60 Hz)	—	230	—	230
	V DC	24	—	24
Rated power @ U _{MAX} VA (50 Hz)/W	0.4	7.5/0.9	0.4	7.5/0.9
Operating range V AC (50/60 Hz)	—	40...280	—	40...280
	V DC	4...32	—	4...32
Must drop-out voltage V AC (50/60 Hz)/DC	—/2	6/—	—/2	6/—
Technical data				
Electrical life cycles	10 · 10 ⁶		10 · 10 ⁶	
Operate/release time ms	< 10/< 10	< 10/< 30	< 1/< 10	< 2/< 25
Insulation between input and output (1.2/50 µs) kV	6		6	
Ambient temperature °C	-20...+80**		-20...+80**	
Protection category	IP 20		IP 20	
Approvals (according to type)	   			

77.31.x.xxx.8050**Zero-crossing switch-on
Suggested applications:**

- Lamp inrush current reduction (CFL - Compact Fluorescent energy-saving Lamps and similar)
- Heater control
- Solenoid, contactor driver

**77.31.x.xxx.8051****Random switch-on
Suggested applications:**

- Finer control requiring short operate time (specially motor control)



30 A modular SSR, 1 NO output

- 22.5 mm housing, heat-sink + plastic cover
- 60 to 440 V AC output (with back to back SCR)
- 6 kV (1.2/50 µs) insulation between Input and Output
- Zero-crossing and random switch-on versions available
- High switching speed
- High endurance
- Silent switching
- Spark and bounce-free switching
- Low control power
- 3-phase general purpose
- "Contactor-style" terminal arrangement (input and output terminals on adjacent sides)
- 35 mm rail (EN 60715) mount

77.31

Screw terminal



* See L77-5 diagram page 11

** See L77-4 diagrams page 10

For outline drawing see page 14

Output specification

Output configuration	1 NO (SPST-NO)	1 NO (SPST-NO)
Rated current I_N /Max. peak current* (10 ms) A	30/520*	30/520*
Rated voltage V AC (50/60 Hz)	400	400
Switching voltage range V AC (50/60 Hz)	48...480	48...480
Repetitive peak off-state voltage V_{pk}	1100	1100
Rated load AC7a ($\cos \varphi = 0.8$) A	30	30
Rated load AC15 A	20	20
Single phase motor rating (230 V AC) kW	—	1.5
Nominal lamp rating:		
230 V incandescent/halogen W	6000	4500
fluorescent tubes with electronic ballast W	6000	4000
fluorescent tubes with electromechanical ballast W	3000	1800
CFL W	4000	2500
230 V LED W	4000	2500
LV halogen or LED with electronic ballast W	4000	2500
LV halogen or LED with electromechanical ballast W	4000	2500
Minimum switching current @ 400 V mA	300	300
Typical "OFF-state" leakage current @ 400 V mA	1	1
Max "ON-state" voltage drop @ 25 °C and 30 A V	0.85	0.85
Power loss @ 30 A W	16	16

Input specification

Nominal voltage (U_N)	V AC (50/60 Hz)	—	230	—	230
	V DC	24	—	24	—
Rated power	VA (50 Hz)/W	0.4	7.5/0.9	0.4	7.5/0.9
Operating range	V AC (50/60 Hz)	—	40...280	—	40...280
	V DC	4...32	—	4...32	—
Must drop-out voltage	V AC (50/60 Hz)/DC	—/2	6/—	—/2	6/—

Technical data

Electrical life	cycles	10 · 10 ⁶		10 · 10 ⁶	
Operate/release time	ms	< 10/< 10	< 10/< 30	< 1/< 10	< 2/< 25
Insulation between input and output (1.2/50 µs)	kV	6	6	-20...+80**	-20...+80**
Ambient temperature	°C	IP 20	IP 20	IP 20	IP 20
Protection category					
Approvals (according to type)					


77.31.x.xxx.8070



Zero-crossing switch-on

Suggested applications:

- Lamp inrush current reduction (CFL - Compact Fluorescent energy-saving Lamps and similar)
- Heater control
- Solenoid, contactor driver




77.31.x.xxx.8071



Random switch-on

Suggested applications:

- Fine controls involving shorter time (specially motor control)



**25, 40 And 50 A panel SSR,
"hockey puck" style**

- "hockey puck" housing with cover
- 24 to 240 V AC output
- Zero-crossing version
- High switching speed
- High endurance
- Silent switching
- Spark and bounce-free switching
- Low control power
- 3-phase general purpose
- "Relay-style" terminal arrangement (input and output terminals on opposite sides)
- Mounting on heatsink with screws

77x5
Screw terminal (plate clamp)

D



* See L77-11 diagrams page 11

** See L77-8, L77-9 and L77-10 diagrams page 11




For outline drawing see page 14

Output specification

Output configuration	1 NO (SPST-NO)	1 NO (SPST-NO)	1 NO (SPST-NO)	
Rated current I_N /Max. peak current* (10 ms) A	25/300*	40/500*	50/520*	
Rated voltage V AC (50/60 Hz)	230	230	230	
Switching voltage range V AC (50/60 Hz)	21.6...280	21.6...280	21.6...280	
Repetitive peak off-state voltage V_{pk}	600	600	600	
Nominal lamp rating:				
230 V incandescent/halogen W	2000	4000	6000	
fluorescent tubes with electronic ballast W	2000	4000	6000	
fluorescent tubes with electromechanical ballast W	1000	2000	3000	
CFL W	800	3000	4000	
230 V LED W	800	3000	4000	
LV halogen or LED with electronic ballast W	800	3000	4000	
LV halogen or LED with electromechanical ballast W	1000	3000	4000	
Minimum switching current @ 250 V mA	120	250	250	
Typical "OFF-state" leakage current @ 250 V mA	10	10	10	
Max "ON-state" voltage drop @ 25 °C and I_N V	1.6	1.6	1.6	
Power loss @ I_N W	40	64	80	
Input specification				
Nominal voltage (U_N) V AC (50/60 Hz)	—	230	—	230
	V DC	24	—	24
Rated power @ U_{MAX} VA (50 Hz)/W	—/0.6	2.4/—	—/0.6	2.4/—
Operating range V AC (50/60 Hz)	—	90...280	—	90...280
	V DC	3...32	—	3...32
Must drop-out voltage V AC (50/60 Hz)/DC	—/1	10/—	—/1	10/—

Technical data

Electrical life cycles	10 · 10 ⁶		10 · 10 ⁶		10 · 10 ⁶	
Operate/release time ms	10/10	40/80	10/10	40/80	10/10	40/80
Insulation between input and output (1.2/50 µs) kV	5.6		5.6		5.6	
Ambient temperature °C	−30...+80**		−30...+80**		−30...+80**	
Protection category	IP 20		IP 20		IP 20	
Approvals (according to type)	  					

77.25.x.xxx.8250**77.45.x.xxx.8250****77.55.x.xxx.8250**

Simplified circuit diagram

Simplified circuit diagram

Simplified circuit diagram

**25, 40 And 50 A panel SSR,
"hockey puck" style**

- "hockey puck" housing with cover
- 48 to 600 V AC output
- Zero-crossing version
- High switching speed
- High endurance
- Silent switching
- Spark and bounce-free switching
- Low control power
- 3-phase general purpose
- "Relay-style" terminal arrangement (input and output terminals on opposite sides)
- Mounting on heatsink with screws

77.x5
Screw terminal (plate clamp)



* See L77-11 diagrams page 11

** See L77-8, L77-9 and L77-10 diagrams page 11

For outline drawing see page 14

Output specification




Output configuration	1 NO (SPST-NO)	1 NO (SPST-NO)	1 NO (SPST-NO)
Rated current I_N /Max. peak current* (10 ms) A	25/300*	40/500*	50/520*
Rated voltage V AC (50/60 Hz)	600	600	600
Switching voltage range V AC (50/60 Hz)	43.2...660	43.2...660	43.2...660
Repetitive peak off-state voltage V_{pk}	1200	1200	1200
Nominal lamp rating:			
230 V incandescent/halogen W	2000	4000	6000
fluorescent tubes with electronic ballast W	2000	4000	6000
fluorescent tubes with electromechanical ballast W	1000	2000	3000
CFL W	800	3000	4000
230 V LED W	800	3000	4000
LV halogen or LED with electronic ballast W	800	3000	4000
LV halogen or LED with electromechanical ballast W	1000	3000	4000
Minimum switching current @ 250 V mA	120	250	250
Typical "OFF-state" leakage current @ 250 V mA	10	10	10
Max "ON-state" voltage drop @ 25 °C and I_N V	1.6	1.6	1.6
Power loss @ I_N W	40	64	80

Input specification

Nominal voltage (U_N)	V AC (50/60 Hz)	—	230	—	230	—	230
	V DC	24	—	24	—	24	—
Rated power @ U_{MAX}	VA (50 Hz)/W	—/0.6	2.4/—	—/0.6	2.4/—	—/0.6	2.4/—
Operating range	V AC (50/60 Hz)	—	90...280	—	90...280	—	90...280
	V DC	4...32	—	4...32	—	4...32	—
Must drop-out voltage	V AC (50/60 Hz)/DC	—/1	10/—	—/1	10/—	—/1	10/—

Technical data

Electrical life	cycles	10 · 10 ⁶		10 · 10 ⁶		10 · 10 ⁶	
Operate/release time	ms	10/10	40/80	10/10	40/80	10/10	40/80
Insulation between input and output (1.2/50 µs)	kV	5.6		5.6		5.6	
Ambient temperature	°C	−30...+80**		−30...+80**		−30...+80**	
Protection category		IP 20		IP 20		IP 20	
Approvals (according to type)		   					

77.25.x.xxx.8650**77.45.x.xxx.8650****77.55.x.xxx.8650**

Ordering information

Example: 77 series modular SSR, 1 output 30 A AC, input voltage 230 V AC, relay style terminals arrangement, zero-crossing switch-on.

Series	7	7	.	3	1	.	8	.	2	3	0	.	8	A	B	C	D
Type/rated current																	
0 = 5/7/15 A output (77.01)																	
1 = 15 A output (77.11)																	
2 = 25 A output (77.25)																	
3 = 30 A output (77.31)																	
4 = 40 A output (77.45)																	
5 = 50 A output (77.55)																	
No. of poles/mounting																	
1 = 1 pole, modular housing (plastic or heat sink/plastic), DIN rail mounting																	
5 = 1 pole, heat-sink or directly panel mounting ("hockey puck")																	
D Input version																	
0 = DC/AC (50/60 Hz)																	
8 = AC (50/60 Hz)																	
9 = DC																	
Supply voltage																	
See "input specification"																	

Codes/Module width

77.01.8.230.8050/17.5 mm	5 A	77.11.8.230.8250/22.5 mm	15 A	77.31.8.230.8050/22.5 mm	30 A	77.25.8.230.8250/hockey puck	25 A
77.01.0.024.8050/17.5 mm	5 A	77.11.9.024.8250/22.5 mm	15 A	77.31.9.024.8050/22.5 mm	30 A	77.25.9.024.8250/hockey puck	25 A
77.01.8.230.8051/17.5 mm	5 A	77.11.8.230.8251/22.5 mm	15 A	77.31.8.230.8051/22.5 mm	30 A	77.25.8.230.8650/hockey puck	25 A
77.01.0.024.8051/17.5 mm	5 A	77.11.9.024.8251/22.5 mm	15 A	77.31.9.024.8051/22.5 mm	30 A	77.25.9.024.8650/hockey puck	25 A
77.01.9.024.9125/17.5 mm	7 A	77.11.8.230.8070/22.5 mm	30 A	77.31.8.230.8070/22.5 mm	30 A	77.45.8.230.8250/hockey puck	40 A
77.01.9.024.9024/17.5 mm	15 A	77.11.9.024.8070/22.5 mm	30 A	77.31.9.024.8070/22.5 mm	30 A	77.45.9.024.8250/hockey puck	40 A
		77.11.8.230.8071/22.5 mm	30 A	77.31.8.230.8071/22.5 mm	30 A	77.45.8.230.8650/hockey puck	40 A
		77.11.9.024.8071/22.5 mm	30 A	77.31.9.024.8071/22.5 mm	30 A	77.45.9.024.8650/hockey puck	40 A

Technical data

		77.01.8xxx	77.01.9xxx	77.11	77.31	72.25/45/55			
		Dielectric strength (1.2/50 µs)	Impulse (1.2/50 µs)						
Between input and output		2500 V AC	5 kV	3000 V AC	4 kV	3000 V AC	6 kV	3000 V AC	6 kV
Between input and ground (heat-sink)		—	—	—	—	3000 V AC	6 kV	4000 V AC	5.6 kV
Between output and ground (heat-sink)		—	—	—	—	2500 V AC	4 kV	4000 V AC	5.6 kV
EMC specifications	Reference standard	77.01.8xxx	77.01.9xxx	77.11	77.31	72.25/45/55			
		24 V AC/DC	230 V AC	24 V DC	24 V AC/DC	230 V AC	24 V AC/DC	230 V AC	24 V AC/DC - 230 V AC
Electrostatic discharge	contact discharge	EN 61000-4-2		4 kV		4 kV		4 kV	
	air discharge	EN 61000-4-2		8 kV		8 kV		8 kV	
Radiated electromagnetic field (80...1000 MHz)	EN 61000-4-3		30 V/m	—	20 V/m		30 V/m	—	
Fast transients on supply terminals (burst 5/50 ns, 5 and 100 kHz)	EN 61000-4-4	1 kV	4 kV	2 kV	1 kV	3 kV	1 kV	3 kV	2 kV
Voltage pulses on supply terminals (surge 1.2/50 µs)	common mode	EN 61000-4-5	2 kV	4 kV	1 kV	3 kV	3 kV	3 kV	2 kV
	differential mode	EN 61000-4-5	1 kV	4 kV	0.5 kV	0.5 kV	1.5 kV	0.5 kV	1 kV
Radio-frequency common mode voltage (0.15...230 MHz) on supply terminals	EN 61000-4-6	—	—	10 V	10 V	10 V	10 V	—	—
Terminals		77.01.8xxx	77.01.9xxx	77.11	77.31	72.25/45/55			
Screw torque	Nm	0.8	0.8	0.8	0.8	0.8	0.8	0.5	1.2
Max. wire size		solid cable	stranded cable	solid cable	stranded cable	solid cable	stranded cable	solid and stranded cable	
	mm ²	1x6 / 2x4	1x4 / 2x25	1x6 / 2x4	1x4 / 2x25	1x6 / 2x4	1x6 / 2x4	1 (with ferrule)	4 (with ferrule) 10 (with fork tip)
	AWG	1x10 / 2x12	1x12 / 2x14	1x10 / 2x12	1x12 / 2x14	1x10 / 2x12	1x10 / 2x12	18 (with ferrule)	12 (with ferrule) 8 (with fork tip)
Wire strip length	mm	9	9	9	9	9	10	10	
Other data									
Power lost to the environment	without output current	W	0.5	0.5	0.9	0.9	0.9	0.6	
	with rated current	W	4.0	4.0	14	16	40/64/80		

Input specification

77.01

Nominal voltage	Input code	Operating range				Must drop-out voltage (AC/DC)	Input current I _N at U _N		
		AC		DC					
		U _{min}	U _{max}	U _{min}	U _{max}				
U _N									
V	0.024	16	32	9.8	32	2.4	25		
24	9.024	—	—	4	32	3.0	18		
230	8.230	90	265	—	—	24	15		

77.11

Nominal voltage	Input code	Operating range				Must drop-out voltage (AC/DC)	Input current I _N at U _N		
		AC		DC					
		U _{min}	U _{max}	U _{min}	U _{max}				
U _N									
V	0.024	—	—	4	32	2	11		
24	9.024	—	—	—	—	6	25		
230	8.230	40	305	—	—				

77.31

Nominal voltage	Input code	Operating range				Must drop-out voltage (AC/DC)	Input current I _N at U _N		
		AC		DC					
		U _{min}	U _{max}	U _{min}	U _{max}				
U _N									
V	0.024	—	—	4	32	2	11		
24	9.024	—	—	—	—	6	25		
230	8.230	40	280	—	—				

77.x5.x.xxx.8250

Nominal voltage	Input code	Operating range				Must drop-out voltage (AC/DC)	Input current		
		AC		DC					
		U _{min}	U _{max}	U _{min}	U _{max}				
U _N									
V	0.024	—	—	4	32	2	11		
24	9.024	—	—	3	32	1	22		
230	8.230	90	280	—	—	10	20		

77.x5.x.xxx.8650

Nominal voltage	Input code	Operating range				Must drop-out voltage (AC/DC)	Input current I _N at U _N		
		AC		DC					
		U _{min}	U _{max}	U _{min}	U _{max}				
U _N									
V	0.024	—	—	4	32	1	25		
24	9.024	—	—	—	—	10	10		
230	8.230	90	280	—	—				

Led indication

LED	Supply voltage
_____	OFF
	ON


LED (77.01.9.024.9xxx only)	Short circuit*
_____	NO
	YES

* To restore normal operation it is necessary to disconnect the power, resolve the short circuit and then restore power.


D

Output specification

L77-1 Output RMS current v ambient temperature
77.01.0.024.805x @ 32 V DC



L77-2 Output RMS current v ambient temperature
77.01.8.230.805x @ 265 V AC




D  I - Modular SSR installed as a group (without gap)


II - Modular SSR installed as a group (9 mm gap between each SSR)

III - Modular SSR installed individually in free air (without a significant influence from nearby components)

L77-12 Output DC current v ambient temperature
77.01.9.024.9024 @ 32 V DC




L77-13 Output DC current v ambient temperature
77.01.9.024.9125 @ 32 V DC




I - Modular SSR installed as a group (without gap)

II - Modular SSR installed individually in free air , or with a gap ≥ 9 mm, which implies a not significant influence from nearby components

L77-6 Output RMS current v ambient temperature
77.11.x.xxx.82xx



L77-4 Output RMS current v ambient temperature
77.31.x.xxx.80xx




I - Modular SSR installed as a group (without gap)

II - Modular SSR installed as a group (20 mm gap between each SSR)
III - Modular SSR installed individually in free air , or with a gap ≥ 40 mm, which implies a not significant influence from nearby components

Output specification


L77-10 Output RMS current v ambient temperature
77.25.x.xxx.8x50



1 - Installation on 077.25 heat-sink (2 K/W)

2 - Installation individually in free-air


L77-9 Output RMS current v ambient temperature
77.45.x.xxx.8x50



1 - Installation on 077.55 heat-sink (0.9 K/W)


2 - Installation individually in free-air

L77-8 Output RMS current v ambient temperature
77.55.x.xxx.8x50




L77-3 Inrush peak current (AC) v inrush time

77.01.x.xxx.80xx



L77-5 Inrush peak current (AC) v inrush time

77.31.x.xxx.80xx




1 - Cold" conditions (ambient temperature = 23 °C, no output current during the last 15 minutes)

2 - "Hot" conditions (ambient temperature = 50 °C, rated output current)


L77-7 Inrush peak current (AC) v inrush time

77.11.x.xxx.82xx



L77-11 Inrush peak current (AC) v inrush time

77x5.x.xxx.8x50



Output specification

Load	77.01.8xxx	77.01.9xxx	77.11	77.31	77.25	77.45	77.55
5 A 230 V (AC1)	5000	—	—	—	—	—	—
5 A 24 V DC L/R = 20 ms	—	3600	—	—	—	—	—
1 A (AC15)	10000	—	—	—	—	—	—
0.5 A (AC15)	20000	—	—	—	—	—	—
15 A 305 V cos φ = 0.8	—	—	1800	—	—	—	—
15 A 305 V cos φ = 0.5	—	—	1200	—	—	—	—
30 A 480 V cos φ = 0.8	—	—	—	1800	—	—	—
30 A 480 V cos φ = 0.5	—	—	—	1200	—	—	—
25 A 230 V cos φ = 0.7	—	—	—	—	1800	—	—
40 A 230 V cos φ = 0.7	—	—	—	—	—	1800	—
50 A 230 V cos φ = 0.7	—	—	—	—	—	—	1800

D	Other data							
	77.01.8xxx	77.01.9xxx	77.11	77.31	77.25	77.45	77.55	
Critical rising voltage dv/dt without input control (gate open) @ T _j = 125 °C	> 1000 V/μs	> 1000 V/μs	> 500 V/μs > 10 V/μs (with di/dt = 20 A/ms)	> 1000 V/μs	300 V/μs .8250)	500 V/μs .8250)	1000 V/μs .8250)	1000 V/μs .8250)
Critical rising current di/dt @ T _j = 125 °C	> 50 A/μs	> 50 A/μs	> 50 A/μs	> 150 A/μs	—	—	—	—
I²t for fusing @ t _p = 10 ms	450 A ² s	450 A ² s	1000 A ² s*	1350 A ² s**	450 A ² s	1250 A ² s	1350 A ² s	1350 A ² s


Suggested fuse (depending on application) for short-circuit protection (Ultra-Fast acting types for semiconductors):

* 20 A, 660 V AC, 10 x 38 mm, 200 kA, 360 A²s.


** 30 A, 660 V AC, 10 x 38 mm, 200 kA, 1000 A²s.

Wiring diagrams


**Single-phase connection
(77.01....802x)**




**Single-phase connection DC
(77.01....9x2x)**




Single-phase connection (77.11)




**Single-phase connection
(77.31....805x)**




**Single-phase connection
(77.31....807x)**



Single-phase connection (77.x5)



Example of three-phase connection (with 3 x 77.01)




Note: this connection can be used with all 77 series types.

Outline drawings


77.01

Screw terminal

**D**


77.01 DC

Screw terminal




77.11/31

Screw terminal




Screw terminal (plate clamp)



Accessories



020.01




Adaptor for panel mounting, plastic, 17.5 mm wide for 77.01 only

020.01



022.09



022.09



060.48

Sheet of marker tags (CEMBRE Thermal transfer printers) for all relays
(48 tags), 6 x 12 mm

060.48

Accessories





077.25

Heat-sink, anodized aluminium, 2 K/W, 65 x 100 mm, for 77.25 only

077.25

- Both the SSR and 35 mm rail clip mount to the heat-sink using M4 screws (supplied with heat-sink)
- Before assembling to the heat-sink, it is necessary to apply a thin and even layer of thermal conductive paste (not supplied) to the lower metal surface of the SSR



077.25 with 77.25





077.55

Heat-sink, anodized aluminium, 0.9 K/W, 111 x 100 mm, for 77.45 and 77.55

077.55

- Both the SSR and 35 mm rail clip mount to the heat-sink using M4 screws (supplied with heat-sink)
- Before assembling to the heat-sink, it is necessary to apply a thin and even layer of thermal conductive paste (not supplied) to the lower metal surface of the SSR



077.55 with 77.45/55

