

**H0,75/24T ZH HBL****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

For the following conductors: 2 No. 0.75 mm<sup>2</sup> (2 No. AWG 18)

- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                                                   |
|------------|-------------------------------------------------------------------|
| Version    | Wire-end ferrule, Twin wire-end ferrule, 21 mm, 18 mm, Light Blue |
| Order No.  | <a href="#">9037630000</a>                                        |
| Type       | H0,75/24T ZH HBL                                                  |
| GTIN (EAN) | 4008190493271                                                     |
| Qty.       | 500 pc(s).                                                        |
| Packaging  | loose                                                             |

Creation date October 27, 2021 6:10:22 AM CEST

Catalogue status 22.10.2021 / We reserve the right to make technical changes.

## H0,75/24T ZH HBL

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 0.206 g |
|------------|---------|

## Technical data

|                        |                                   |         |                       |
|------------------------|-----------------------------------|---------|-----------------------|
| Description of article | Twin wire end ferrule, light blue | Version | Twin wire-end ferrule |
|------------------------|-----------------------------------|---------|-----------------------|

## Wire-end ferrules

|                                         |               |                             |                      |
|-----------------------------------------|---------------|-----------------------------|----------------------|
| Collar height (A)                       | 5.5 mm        | Collar width (B)            | 3 mm                 |
| Colour code                             | Telemecanique | Conductor cross-section     | 0.75 mm <sup>2</sup> |
| Contact surface diameter (D1)           | 1.7 mm        | Contact surface length (L2) | 18 mm                |
| L1 in mm                                | 24 mm         | Metal sleeve thickness (S1) | 0.15 mm              |
| Plastic collar thickness (S2)           | 0.3 mm        | Stripping length            | 21 mm                |
| Wire connection cross section AWG, max. | AWG 18        |                             |                      |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ECLASS 9.0  | 27-40-02-01 |
| ECLASS 9.1  | 27-40-02-01 | ECLASS 10.0 | 27-40-02-01 |
| ECLASS 11.0 | 27-40-02-01 |             |             |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E499744 |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                                                                     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>                                                 |
| Brochures          |                                                                                          |

**H0,75/24T ZH HBL****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Drawing**